

SURVEY & REMONUMENTATION

MAY 09 1996

COMMISSION

Liber 000001 Page 0539 *RR*

-copy-

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

M-13 Page 1

For corners in
Wayne *Washington*
 County

Located in:
 YPSILANTI

Corner Code
 M-13
 M-11 ✓

1. Public Land Survey
 T 3 S R 7 E
 T 4 S R 7 E
 T
 T
 T

2. Property Controlling
 in Section S
 T
 T
 T

3. Miscellaneous
 Property in Sec. S
 T
 T
 T

4. Lot No. _____, Recorded Plat _____

5. Private Claims _____

Register of Deeds Stamp and File Number

I, Michael S. Hoben in a field survey on 03/01/1995
 do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management, or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law, established, re-established, monumented, re-monumented, recovered, found as expressed below.

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restorations:

11/24/1816

G.L.O.

POST

NO RECORD FOUND

01/01/1930

W.C.R.C.

MON. (A-13 VANBUREN TWP.)

1 ED. GUY POLE NW. 27.80' (A-13 VANBUREN)

(Witnesses Continued on Back ...)

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

MON IN MON BOX IN ASPH. RD.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

03/01/1995

Hoben

35994

OHM

REMON

- 7 C.L. CATCH BASIN S 51 E 33.23'
- 8 C.L. CATCH BASIN S 51 W 34.70'
- 10 TAG IN DE POLE N 40 E 73.21'
- 11 TAG IN DE POLE N 45 E 82.65'
- 12 SET TAG IN DE POLE S 30 E 158.02'



-copy-
 RECORDS
 COUNTY CLERK/REGISTER

MAR 29 1 50 PM '96

RECORDED
 WASHINGTON COUNTY, MI

We conclude that after careful study of the record documentation and field observations, that this corner is accepted as the best available evidence of the position of the original corner.

Signed by Michael S. Hoben

Date 12-18-95

Drafted by Michael S. Hoben

Surveyor's Michigan License No. 35994

Orchard, Hiltz and McCliment, Inc. 34935 Schoolcraft Road Livonia, MI 48150

(Continued) Description of original monument and accessories and/or subsequent restorations:

01/01/1930	W.C.R.C.	MON. (A-13 VANBUREN TWP.)
2688.74' S. OF W. 1/4 COR. SEC. 31 VANBUREN TWP. (A-12)		
2	ED. POLE NE. 38.17' (A-13 VANBUREN)	
3	NAIL NE. SIDE FENCE POST SE. 35.68' (A-13 VANBUREN)	
4	NAIL NW. SIDE 12" BOX ELDER SW. 61.32' (A-13 VANBUREN)	
5	U.S.G.S. MON. SW. 41.80' (A-13 VANBUREN)	
11/20/1972	J. SNYDER 13352 ATWELL- L.2 P HICKS	FOUND 1/4" RE ROD IN MON. BOX AT C. LINE RD. INT.
6	12" APPLE N.56 W. 61.5'	
7	CATCH BASIN S 51 E. 33.2'	
8	CATCH BASIN S. 51 W. 34.7'	
03/20/1978	R. JAGOW 6998 ATWELL- HICKS	1/4" REROD IN MON. BOX @ CL. INT. RAWSONVILLE & BEMIS
SAME AS ABOVE		

APPROVED

DATE 10/16/95

CO. REP. 12