

**SURVEY
REMONUMENTATION**

APR 29 1999

SECTION

**ALLEGAN COUNTY REMONUMENTATION
LAND-CORNER RECORDATION CERTIFICATE
FILING REQUIREMENT OF ACT 74, MICH. P. A. 1970**

FILED

LIBERO 007 PAGE 98

FOR CORNERS IN:	LOCATED IN:	CORNER CODE #
ALLEGAN COUNTY		
1. Public Land Survey	T.....1N R.....13W	C-12
1/4 CORNER COMMON TO SECTION 19 & 20	T..... R.....	
TROWBRIDGE TOWNSHIP	T..... R.....	
	T..... R.....	
2. Property Controlling in section	S.....T.....R.....	
	S.....T.....R.....	
3. Miscellaneous Property in Sec.	S.....T.....R.....	
4. Lot No....., Recorded Plat.....		
5. Private Claims.....		

1/28/1999 2:44:39 PM

JOYCE A. WATTS
REGISTER OF DEEDS
ALLEGAN COUNTY, MICH

REGISTER OF DEEDS STAMP & FILE NUMBER

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

I, Raymond Moored in a field survey on Sept. 23, 1998 do hereby state that under requirements of P.A 74, Michigan P.A of 1970, corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior Bureau of Land management or by a decree of a Court of Law and/or that the corner points mentioned in the lines 3, 4, and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law established, monumented, recovered, found as expressed below.

Note: Not more than 2 corners, all the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

- G.L.O. 40.00 SET QR SEC POST
BEECH 18 S4E 23
BEECH 18 N7W 16
- D. RATEKIN, L.C.R.C. RECORDED IN L. 1, P. 207, DATED: 04-18-1972
(SAME INFORMATION RECORDED SURVEY BY RATEKIN, L. 816, P. 13, DATED: 07-12-1972)
1" IRON NEXT TO STONE
-4" WILD CHERRY (NAIL & RIBBON) N40°W 8.7'
-4" WILD CHERRY (NAIL & RIBBON) EAST 25.4'
-FENCE CORNER POST S45°W 0.8'

APPROVED REMONUMENTATION CORNER
P.A. 345 OF 1990
ALLEGAN COUNTY

DATE APPROVED NOV 24, 1998
COUNTY REP. *[Signature]*

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

FOUND 1" IRON AND STONE AT BASE OF ROTTED FENCE CORNER POST PER NUMBER 2 LISTED ABOVE.
SET 3/4" X 24" ALLEGAN COUNTY REMON IRON W/REMON CAP IN PLACE OF FOUND CORNER.

ACCEPTED POSITION AS A CAREFUL AND FAITHFUL PERPETUATION OF THE POSITION OF THE ORIGINAL CORNER.
APPROVED BY ALLEGAN COUNTY REMONUMENTATION PEER GROUP ON NOV. 24, 1998

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

SET STANDARD ALLEGAN COUNTY REMONUMENTATION IRON WITH CAP.

- NAIL & TAG IN S SIDE 12" ELM N80°E 1'
- NAIL & TAG IN S SIDE 12" TW. ELM N90°W 9.55'
- NAIL & TAG IN NE SIDE 10" MAPLE N40°W 16.65'
- NAIL & TAG IN WEST SIDE 16" MAPLE N30°E 16.5'

C-13 S0°36'50"E 2658.58' D-12 S89°57'49"E 2616.94'
C-11 N0°36'50"W 2651.41'

Raymond E. Moored Date 12/1/98

Surveyors License No. 26463

