

SURVEY & REMONUMENTATION

APR 29 1996

ALLEGAN COUNTY REMONUMENTATION LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

For County of Allegan
(County)

	Located In:	Corner Code #:
1. Public Land Survey	T <u>2</u> N R <u>11</u> W	D-13 (S1,32)
	T ___ R ___	Martin
	T ___ R ___	_____
	T ___ R ___	_____
2. Property Controlling in Section	S ___ T ___ R ___	_____
	S ___ T ___ R ___	_____
3. Miscellaneous Property in Sec.	S ___ T ___ R ___	_____
	S ___ T ___ R ___	_____
4. Lot No. _____, Recorded Plat _____		
5. Private Claims _____		

REGISTER OF DEEDS
 ALLEGAN COUNTY, MICH.
James C. Batten

1995 APR 24 PM 2:20

FILED

Register of Deeds Stamp & File Number

I, David F. Peabody, in a field survey on November 10, 1994, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:
 G.L.O. (Set Post) Wightman Moored, INC. 1992
 W. Oak 14 N48E 20 (Same as Ratekin's 1973)
 Do. 12 N65½W 25

Ratekin LCRC (L.02, P.126) 1973
 Set 1" Iron
 West End 12" CMP N20°E 28.6'
 East End 12" CMP N60°E 47.13'
 P. Pole N3°W 52.13'
 8" Oak N25°E 107.9' and 28" Oak S25°E 35.45'


B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:
 Found 1" Solid Iron
 G.L.O. All Gone
 All Ratekin 1973 & Wightman Moored, INC. 1992 Accessories were located & used except 28" Oak S25°E 35.45'

And is accepted as a careful and faithful perpetuation of the position of the original corner.

APPROVED REMONUMENTATION CORNER
 P.A. 345 OF 1990
 ALLEGAN COUNTY
 DATE APPROVED 11-8-94
 COUNTY REP. *David F. Peabody*

Peer Group Approved 11-08-94

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:
 Placed Remon Cap over 1" Iron
 20d Nail W/Allegan Co. Tag E. Side P. Pole N5°W 52.75'
 20d Nail W/Allegan Co. Tag SW Side 30" Oak S60°E 67.19'
 FG. Nail W. Side 9" Beech S10°E 32.31'
 20d Nail W/Allegan Co. Tag SW Side 8" Hickory N40°W 38.94'
 N1/4 Sec. 5 (Gun Plain Twp.) D-1 West 148.60'
 C/L Rd. North 1.5'±



LIB: 0005 PAGE 170

Signed by David F. Peabody Date 11/26/95
 Surveyor's Michigan License No. 25866