

**Allegan County Remonumentation  
LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970**

For corners in

Allegan Co. Located In: Hopkins Corner Code #  
(County) Twp.

1. Public Land Survey	T	R	
	T	R	C-1
	T	R	
	T	R	
2. Property Controlling in Section	S	T	R
	S	T	R
3. Miscellaneous Property in Sec.	S	T	R
	S	T	R

*Robert J. Jonker*  
Professional Surveyor  
No. 21572

1995 DEC 14 PM 2:34

FILED

Register of Deeds Stamp & File Number

**SURVEY &  
REMONUMENTATION**

APR 29 1996

COMMISSION

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_  
5. Private Claims \_\_\_\_\_

A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1						
3												
4	7	8	9	10	11	12						
5												
6	16	17	15	14	13							
7												
8	19	20	21	22	23	24						
9												
10	30	29	28	27	26	25						
11												
12	31	32	33	34	35	36						
13												

I, Robert J. Jonker in a field survey on December 13, 19 94 do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

G.L.O., 77.5 ch. Intersect N. boundary 20 lks. E. of post and set post corner Sec. 5 & 6  
Sugar 16 S 31 W 17  
Beech 6 S 50 E 8

(over)

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found stone 0.22' South of twp. line, with 1/2" iron bent over the top.  
Found iron and stone by all witnesses listed on the reverse side.

APPROVED REMONUMENTATION CORNER  
P.A. 345 OF 1990  
ALLEGAN COUNTY  
DATE APPROVED 12-14-95  
COUNTY REP. Robert J. Jonker

This monument is accepted by myself to be a careful and faithful perpetuation of the position of the corner.


Peer group approved on 12-14-95.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Replaced with 3/4" x 36" standard capped Allegan County monument on twp. line in gravel road.  
A/C tag on S. side P. pole East 67.71'  
A/C tag on W. side 30" Maple S 30° W 61.97'  
A/C tag on E. side P. pole N 35° W 74.65'  
A/C tag on W. side P. pole N 30° E 147.39'  
A/C tag on W. side 16" Maple S 20° W 97.58'  
SE cor. Sec. 31, T4N, R12W West 13.20'

(over for Sheet 2)

Signed by Robert J. Jonker Date December 14, 1995  
Surveyor's Michigan License No. JONKER LAND SURVEYS, P.C. 21572



0005 PAGE 225

1 OF 2

1972, survey by Ratekin, recorded in L. 816, Pg. 09  
Shows jog of 13.26'

1979, Ratekin, again in 1981  
County road comm. finds iron 14.7' East of Dorr corner, survey notes indicate  
large stone on jog distance - Ratekin is using jog, iron may be on E. side of  
stone.

C/L gravel road West 10'±  
Higher PK in Ne side P. pole NW 74.97'  
PK - S. side P. pole E 67.78'  
PK - SE side 37" Maple SW 44.91'  
PK - SE side 40" Maple SSW 62.31'

Wightman Moored - 1992  
Found ½" pipe on C/L stone