

ALLEGAN COUNTY REMONUMENTATION
 LAND CORNER RECORDATION CERTIFICATE
 Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Allegan (County) Located in: Corner Code #

1. Public Land Survey T 3N R 14W J-9 (S 1/4, 23)
 T R Heath Twp.
 T R
 T R

2. Property Controlling S T R
 in Section S T R
 3. Miscellaneous S T R
 Property in Sec. S T R

4. Lot No. _____, Recorded Plat _____
 5. Private Claims _____

97 JAN 22 PM 1:23
 REGISTER OF DEEDS
 ALLEGAN COUNTY, MICHIGAN
 FIN EN
 Register of Deeds Stamp & File Number

I, Kirk L. Van Order, in a field survey on Oct. 10, 1993 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and for that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law, established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

1	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	10	11	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

A. Description of original monument and accessories and/or subsequent restoration:

- J-9
 (1) GLO West correct line between Sec. 23 & 26
 39.55 Set 1/4 Sec. post
 W. Oak 16" dia. S37E 16 links
 R. Oak 8" dia. N8E 41 links
 (2) Kirk L. Van Order survey dated July 10, 1987
 Set capped iron on line and midway between I-9 and K-9.
 (continued on back of sheet)

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

J-9
 Fd. capped iron #23520 using info. from Kirk L. Van Order survey dated July 10, 1987

And is accepted as a careful and faithful perpetuation of the position of the original corner.

Peer group approved Jan. 10, 1995.

APPROVED REMONUMENTATION CORNER
 P.A. 345 OF 1990
 ALLEGAN COUNTY
 DATE APPROVED 1-10-95
 COUNTY REP. Kirk L. Van Order

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

J-9
 Removed capped iron and set standard Allegan Co. Remon. monument (3/4" x 24" steel rod w/red cap #23520)
 Nail & Remon. tag in E side 9" Maple N,NE 66.37'
 Nail & Remon. tag in SW side 11" W Oak SE 81.00'
 Nail & Remon. tag in SE side 9" W Pine SW 77.58'
 Nail & Remon. tag in SW side 13" R Oak NW 76.38'

Signed by Kirk L. Van Order
 Surveyor's Michigan License No. 23520

Date 12-31-96



FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 17, 1971
 REVISED BY 4, 1975
 REVISOR 1, 1983
 OCT., 1986

MAY 2 1987

1987

Section A (continued from Page 1)

J-9

Heath Twp., T.3N., R.14W.

Measured 5221.47' between I-9 and K-9.

Ties taken:

31" W. Oak	NE	48.43'
15" W. Oak	SE	60.35'
20" Maple	SW	45.48'
8" W. Oak	NW	41.02'
C/L Gravel road	S	5'+/-

Trail to South

(3) Wightman-Moored, Inc. project for A.C.R.C. dated Nov. 11, 1988

Fd. 1/2" iron with K.V.O. cap		
Nail in NW side 17" Soft Maple	S,SW	45.47'
Nail in SW side 15" W Oak	S,SE	60.38'
Nail in NW side 27" Oak	NE	48.43'
Nail in NE side 6" W Oak	N,NW	41.01'
C/L Gravel road	S	4'+/-
C/L Trail NE,ly	E	4'+/-
Nail in NW side 7" Poplar	NE	83.73'
Nail in E side 10", 8", 6" Triple Maple	N	65.30'
Nail in W side 15" Oak	S25°E	100.05'