

Allegan County Remonumentation

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in  
Allegan  
(County)

Located in: Corner Code #

- |                                    |   |       |     |                  |
|------------------------------------|---|-------|-----|------------------|
|                                    |   | 4N    | 11W | G-7 (SE cor. 16) |
| 1. Public Land Survey              | T | _____ | R   | _____            |
|                                    | T | _____ | R   | _____            |
|                                    | T | _____ | R   | _____            |
|                                    | T | _____ | R   | _____            |
| 2. Property Controlling in Section | S | _____ | T   | _____            |
|                                    | S | _____ | T   | _____            |
| 3. Miscellaneous Property in Sec.  | S | _____ | T   | _____            |
|                                    | S | _____ | T   | _____            |

REGISTERED  
ALLEGAN COUNTY  
 97 JAN 22 PM 1:25  
 FILED

Register of Deeds Stamp & File Number

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_  
5. Private Claims \_\_\_\_\_

I, Steven Koertzer, in a field survey on October 3, 1996, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1						
3												
4	7	8	9	10	11	12						
5												
6	13	14	15	16	17	18						
7												
8	19	20	21	22	23	24						
9												
10	25	26	27	28	29	30						
11												
12	31	32	33	34	35	36						
13												

A. Description of original monument and accessories and/or subsequent restoration:

G-7 GLO Sylvester Sibley DS 1831  
Sugar 10 N78E 31  
Becch 8 N75W 4

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

G-7 Found PK nail on C/L 14-4th & on tree row to North & South  
Fnd. spike in E. sdc. 14" Walnut S50°W 31.18'  
Fnd. Spike in W. sdc. 12" dead Elm N20°E 29.28'  
Fnd spike in E. sdc. 12" hickory South 48.60'

This corner is accepted as a careful and faithful perpetuation of the position of the original corner.  
Peer Group approval November 12, 1996.


APPROVED REMONUMENTATION CORNER  
P.A. 345 OF 1990  
ALLEGAN COUNTY  
DATE APPROVED 11-12-96  
COUNTY REP. Rich L. Van Cester

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

G-7 Replaced PK with Allegan Co. Mon. ( 3/4" x 24" Iron Rod with Remonumentation cap)  
Nail & Allegan Co. Remon. Tag in E. side 12" Hickory S2°E 59.42'  
Set 3/4" x 24" Allegan Co. Remon. Iron Rod and Remon. witness cap S40°W 66.95'  
Set 3/4" x 24" Allegan Co. Remon. Iron Rod and Remon. witness cap N20°W 58.07'  
Set 3/4" x 24" Allegan Co. Remon. Iron Rod and Remon. witness cap N15°E 52.95'  
F-7, T4N, R11W 2656.64'  
H-7, T4N, R11W 2647.11'

Signed by [Signature]  
Surveyor's Michigan License No. 39085

Date 12-10-1996



0005 PAGE 439