

COPY

Allegan County Remonumentation  
LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

COMMISSION  
For corners in  
Allegan  
(County)

Located In: Corner Code #

- 1. Public Land Survey
 

|   |    |   |     |   |               |
|---|----|---|-----|---|---------------|
| T | 4N | R | 12W | * | I-13 (SW, 35) |
| T |    | R |     |   | Dorr Twp.     |
| T | 3N | R | 12W | * | I-1 (NE, 3)   |
| T |    | R |     |   | Hopkins Twp.  |
- 2. Property Controlling in Section
 

|   |  |   |   |  |  |
|---|--|---|---|--|--|
| S |  | T | R |  |  |
| S |  | T | R |  |  |
- 3. Miscellaneous Property in Sec.
 

|   |  |   |   |  |  |
|---|--|---|---|--|--|
| S |  | T | R |  |  |
| S |  | T | R |  |  |
- 4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_
- 5. Private Claims \_\_\_\_\_

97 JAN 22 PM 1:26  
 REGISTER OF DEEDS  
 ALLEGAN COUNTY, MICH.  
 REGISTER OF DEEDS STAMP & FILE NUMBER

| A  | B  | C  | D  | E  | F  | G  | H | J | K | L | M |
|----|----|----|----|----|----|----|---|---|---|---|---|
| 2  | 6  | 5  | 4  | 3  | 2  | 1  |   |   |   |   |   |
| 3  |    |    |    |    |    |    |   |   |   |   |   |
| 4  | 7  | 6  | 5  | 4  | 3  | 2  | 1 |   |   |   |   |
| 5  |    |    |    |    |    |    |   |   |   |   |   |
| 6  | 16 | 17 | 16 | 15 | 14 | 13 |   |   |   |   |   |
| 7  |    |    |    |    |    |    |   |   |   |   |   |
| 8  | 18 | 20 | 21 | 22 | 23 | 24 |   |   |   |   |   |
| 9  |    |    |    |    |    |    |   |   |   |   |   |
| 10 | 30 | 29 | 28 | 27 | 26 | 25 |   |   |   |   |   |
| 11 |    |    |    |    |    |    |   |   |   |   |   |
| 12 | 31 | 32 | 33 | 34 | 35 | 36 |   |   |   |   |   |
| 13 |    |    |    |    |    |    |   |   |   |   |   |

I, John C. Bueche, in a field survey on October 1, 1996, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law, established, re-established, monumented, re-monumented, recovered, found as expressed below:


NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

- A. Description of original monument and accessories and/or subsequent restoration:
- |                            |                                  |
|----------------------------|----------------------------------|
| I-13 & I-1 GLO             | Rob Jonker, 1991                 |
| Lucius Lyon, D.S. 1831     | Capped iron                      |
| Set post cor. Sec. 34 & 35 | Set PK SE side PP N 55 E 86.09'  |
| Beech 10 N 9 W 20          | Stop sign post S 85 W 50.08'     |
| Beech 17 N 33 E 37         | NW cor. hse. fnd. S 30 E 164.40' |
|                            | Stop sign post N 65 E 30.35'     |

- B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:
- I-13 & I-1 Found capped rerod in gravel road
- |                   |                |
|-------------------|----------------|
| PK SE side PP     | N 55 E 86.09'  |
| NW cor. hse. fnd. | S 30 E 164.40' |
- And is accepted as a careful and faithful perpetuation of the position of the original corner.
- Approved by Allegan Co. Peer Group 5/14/96

APPROVED REMONUMENTATION CORNER  
P.A. 345 OF 1990  
ALLEGAN COUNTY  
DATE APPROVED 5-14-96  
COUNTY REP. Rich J. Wainwright

- C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:
- I-13 & I-1 Replaced capped iron rerod with Allegan Co. Mon. 3/4" pin with cap
- |   |                |
|---|----------------|
| NW cor. hse fnd.                            | S 30 E 164.32' |
| Capped JCB iron                             | S 58 W 46.21'  |
| Capped JCB iron                             | N 54 W 58.60'  |
| Nail & Allegan Co. Remon. Tag in SE side PP | N 55 E 86.06'  |
| C/L 16" Apple                               | S 20 E 100.66' |
- On C/L gravel road E-W, C/L gravel road N-S, West 10'



Signed by John C. Bueche  
John C. Bueche, P.S. 13027  
Surveyor's Michigan License No. \_\_\_\_\_

Date 10-14-96

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971  
REVISED MAY 14, 1975  
REVISED JAN., 1983