

APR 04 2000

BARRY COUNTY REMONUMENTATION
LAND CORNER RECORDATION CERTIFICATE
FILING REQUIREMENT OF ACT 74, MICH. P. A. 1970

SECTION

FOR CORNERS IN: BARRY COUNTY
LOCATED IN: CORNER CODE #

1. Public Land Survey T. 1N R. 10W J-9

CORNER COMMON TO SECTIONS 23 & 26 PRAIRIEVILLE TOWNSHIP
T. R. T. R. T. R.

2. Property Controlling in section S. T. R. S. T. R.

3. Miscellaneous Property in Sec. S. T. R.

4. Lot No. Recorded Plat

5. Private Claims

I, Raymond Moored in a field survey on Sept. 23, 1999 do hereby state that under requirements of P.A 74, Michigan P.A of 1970, corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior Bureau of Land management or by a decree of a Court of Law and/or that the corner points mentioned in the lines 3, 4, and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law established, monumented, recovered, found as expressed below.

Note: Not more than 2 corners, all the same town and range, may be recorded on this certificate.

Barcode with number 2823
Page: 1 of 2
12/07/1999 08:36
Darla K. Burghdoff - Barry Co. LCRCR

REGISTER OF DEEDS STAMP & FILE NUMBER

Grid with columns A-L and rows 2-13. Contains numbers 1-36. A dot is present in cell J9.

A. Description of original monument and accessories and/or subsequent restoration:

SEE BACK OF FORM FOR CORNER HISTORY

ACT 345 BARRY COUNTY REMONUMENTATION
APPROVED BY PEER REVIEW AT A MEETING HELD ON
11 OCT 99 BR
BRIAN REYNOLDS COUNTY SURVEYOR

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

FOUND 5/8" IRON AS ESTABLISHED BY McPHERSON IN '65. McPHERSON STATES THAT IRON WAS SET FROM OLD WITNESSES. OLD WITNESSES FROM ROAD COMMISSION ARE STILL EXISTING. CORNER POSITION FROM OLD WITNESSES FALLS S48°W 4.81' FROM McPHERSON CORNER. EXCAVATED AT ALTERNATE POSITION AND FOUND BOAT SPIKE 0.5' BELOW ROAD GRADE. EXCAVATED BELOW BOAT SPIKE AND FOUND 3" CLAY TILE BY CRESSEY APPROX. 2 FEET DEEP. SET STANDARD BARRY COUNTY REMONUMENTATION IRON WITH CAP IN CENTER OF CLAY TILE. THIS POSITION ACCEPTED AS A CAREFUL AND FAITHFUL PERPETUATION OF THE POSITION OF THE ORIGINAL CORNER.

APPROVED BY BARRY COUNTY REMONUMENTATION PEER GROUP ON

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

- STANDARD 3/4" X 24" BARRY COUNTY REMONUMENTATION IRON WITH CAP IN 3" CLAY TILE IN MON BOX
- NAIL IN N SIDE 16" CHERRY EAST 29.52'
- FD. NAIL IN SE SIDE 30" OAK N52E 47.23'
- FD. NAIL IN NW SIDE 25" OAK S30W 39.50'
- SE COR 12" SQ. CONC. FE. POST WEST 25.81'
- NW COR 12" SQ. CONC. FE. POST S58W 32.87'
- EXISTING C/L ROAD EAST 2' +/-
- 5/8" IRON (FALSE COR BY McPHERSON) N50E 4.81'

Raymond Moored Date 11/20/99

Surveyors License No. 26463

