

NOV 18 1997

COMMISSION

CLARE COUNTY REMONUMENTATION

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

RECORDED

# 232-97

97 NOV -4 PM 3:15

REGISTER OF DEEDS  
CLARE COUNTY  
CAROL A. McAULAY

Register of Deeds Stamp & File Number

For corners in

CLARE

(County)

Located in:

Corner Code #

1. Public Land Survey

T 18N R 6W

C-7

T R

T R

T R

2. Property Controlling  
In Section

S

T R

S

T R

3. Miscellaneous  
Property in Sec.

S

T R

S

T R

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_

5. Private Claims \_\_\_\_\_

I, MARK R. ROBISON, in a field survey on July 1, 19 97 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

1848 Lyon  
Set Post Cor. Sec.'s 17,18,19,20  
Wit.-Hemlock 9 N31 1/2E 7  
Pine 18 S41W 30

9-20-78 Lapham LCRC#323  
Fd. 3/4" bar  
Wit.-N15E 81.2 4" Steel Gas Marker  
N30W 37.5 Pow. Pole  
S70W 49.8 8" Maple

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found 3/4" x 13" iron bar and two 1978 witnesses. Measured 2660.30 to D-7 and 5320.1 (GLO 5318.94) to E-7.

APPROVED LAND CORNER  
P.A. 345 of 1990  
Clare County

See dossier for detailed report.

Chairman Paul H. Lapham

Date 9-16-97

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Set 5/8" x 36" rod with Clare County Remonumentation Cap marked P.S.#27458. Accepted as best available evidence of the accepted position of the corner.

Witnesses:  
N30W 37.50', N&T, P.P. (OBT)  
S70W 49.80', N&T, 16" Maple (OBT)  
S36E 89.10', N&T, 9" R. Oak  
N54E 160.84', N&T, 14" R. Oak



Signed by Mark R. Robison

Date 10-31-97

Surveyor's Michigan License No. 27458