

MAR 02 2000

SECTION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

Register's Office }
Gogebic County } ss.

Received for record the
12th day of MAY
A. D. 1999 at 10:45 o'clock
11 m., and recorded in
Liber 7 of CORNERS
on page 124
Ramona Collins Dupont
Register of Deeds

For corners in _____

Gogebic (County) Located In: _____ Corner Code # _____

1. Public Land Survey	T <u>46N</u> R <u>43W</u>	<u>K-3</u>
	T _____ R _____	_____
	T _____ R _____	_____
	T _____ R _____	_____
2. Property Controlling in Section	S _____ T _____ R _____	_____
	S _____ T _____ R _____	_____
3. Miscellaneous Property in Sec.	S _____ T _____ R _____	_____
	S _____ T _____ R _____	_____

4. Lot No. _____, Recorded Plat _____

5. Private Claims _____

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L
2	6	5	4	3	2	1						
3												
4	7	8	9	10	11	12						
5												
6	18	17	16	15	14	13						
7												
8	19	20	21	22	23	24						
9												
10	30	29	28	27	26	25						
11												
12	31	32	33	34	35	36						
13												

Section Corner 1, 2, 11 & 12; T.46 N., R.43 W.

I, Richard L. Drahn in a field survey on April 28, _____, 19 99, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

Corner established by Austin Burt on 9/3/1851. Original B.T.s --- Y. Birch 12" S.46 W. 30 links (19.80') --- Y. Birch 12" N.29 E. 21 links (13.86') --- Paul R. Mack on 4/10/35 recovered the Y. Birch B.T. still scribed. He placed a location poster on a 8" Maple east of the corner.

Richard L. Drahn, RLS 21564 restored the corner position on 6/9/86 from the remains of the two original B.T.s and Macks 1935 tag tree. He set a 2" X 3' iron pipe with a 3" stamped brass cap and the following new B.T.s --- Sugar Maple 9" N.86 W. 8.82' --- Sugar Maple 9" N.11 W. 12.45' --- Sugar Maple 5" S.70 E. 19.17' --- 6" Metal sign rail N.48 E. 2.8' ---.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Corner recorded in Gogebic County Liber 3, Page 19 on 3/4/87.

Recovered the monument as described and the bearing trees as follows:

11"	Sugar Maple	N.88 W.	8.78' (new nail)
11"	Sugar Maple	N.12 W.	12.39'
6"	Sugar Maple	S.71 E.	19.23'
6'	Steel sign rail	N.51 E.	2.89'

Only a series of root holes with Y. Birch bark @ S.46 W. and a depression @ N.29 E. remains from the original B.T.s

Corner research on file with Gogebic County records.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

New bearing tree referenced:

9" Sugar Maple S.08 E. 48.85'

Richard L. Drahn 5/11/99
COUNTY _____



Signed by Richard L. Drahn Date May 2, 1999

Surveyor's Michigan License No. 21564

USFS E-21

124