

MAR 02 2000

SECTION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

Register's Office }
Gogebic County } ss.

For corners in

Gogebic
(County)

Located in:

Corner Code #

1. Public Land Survey

T48N R 46W K-7

T R

T R

T R

2. Property Controlling in Section

S T R

S T R

3. Miscellaneous Property in Sec.

S T R

S T R

Received for record the
22ND day of SEPTEMBER
A. D. 1999 at 1:00 o'clock
P m., and recorded in
Liber 7 of CORNERS
on page 252
Ramona Collins Deputy
Register of Deeds

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

Section Corner, Sections 13, 14, 23, & 24, T48N, R46W

I, John P. Goss, in a field survey on Sept 11 19 99 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

	A	B	C	D	E	F	G	H	I	J	K	L
1												
2	6		5		4		3		2		1	
3												
4	7		8		9		10		11		12	
5												
6	18		17		16		15		14		13	
7												
8	19		20		21		22		23		24	
9												
10	30		29		28		27		26		25	
11												
12	31		32		33		34		35		36	
13												

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

Corner established by Austin Burt, on May 23, 1851. Original corner Fir 8" Original bearing tree: Elm 40" S 25° W 9 links (5.94 ft.) Richard L. Drahn, 21564, on July 30, 1984, restored corner position at record bearing and distance from the remains of the original bearing tree, and natural feature calls. He set a 2" aluminum monument with 3 1/2" aluminum cap, stamped to indicated the corner position. He established the following reference objects: 8" Black Ash - N 17° W - 22.43 ft.; 13" Black Ash - N 72° E - 4.59 ft. 4" Sugar Maple - S 13° W - 14.76 ft.; 6' steel sign - S 68° W - 1.6 ft. He recorded said corner in Liber 2, page 689 of Land Corners.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:
Found Richard L. Drahn monument and accessories.

Act 74 research on file.

Richard L. Drahn 9/21/99
COUNTY REGISTRATION

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

From the found monument I established the following new and existing reference objects:

10" Black Ash	N 17° W	22.40 ft. new nail
15" Black Ash	N 72° E	4.51 ft. new nail
4" Sugar Maple	S 13° W	14.76 ft.
8" Yellow Birch	S 66° W	27.80 ft.
6' steel sign post	S 68° W	1.67 ft. to face

(All measurement taken to nail in side of tree)



Signed by John P. Goss

Surveyor's Michigan License No. 23509

Date Sept. 11, 1999

U.S.F.S. No. N-21