

LAND CORNER RECORDATION CERTIFICATE

Authority: 1970 PA 74, MCL 54.205

Surveyor's Name: Stephan J. Szyszkoski

Field Survey Date: See below

For corner(s) in: Iron County

Original Public Land Survey Corner

Corner Code

S _____	T _____	R _____	_____
S _____	T _____	R _____	_____
S _____	T _____	R _____	_____
S _____	T _____	R _____	_____

Property Corner

1/16 Corner Code

a. S <u>10</u>	T <u>44N</u>	R <u>32W</u>	<u>6</u> (GCDB 460560)
S _____	T _____	R _____	_____
b. S <u>10</u>	T <u>44N</u>	R <u>32W</u>	<u>9</u> (GCDB 460540)
S _____	T _____	R _____	_____

1	A	B	C	D	E	F	G	H	I	J	K	L	M	1
2		6		5		4		3		2		1		2
3														3
4		7		8		9		10		11		12		4
5														5
6		18		17		16		15		14		13		6
7														7
8		19		20		21		22		23		24		8
9														9
10		30		29		28		27		26		25		10
11														11
12		31		32		33		34		35		36		12
13	A	B	C	D	E	F	G	H	I	J	K	L	M	13

Part A. Corner History

- a. Northeast 1/16 corner, Section 10 T44N-R32W. Not previously monumented.
- b. Center-East 1/16 corner, Section 10 T44N-R32W. Not previously monumented.



Part B: Surveyor's Report on Perpetuation, Restoration, Reestablishment, or Monumentation of Corner

- a. May 7 2018. Established the position for the corner at the intersection of straight lines connecting opposite 1/16 corners, all monumented.
- b. May 7 2018. Established the position for the corner midway and on a straight line between Quarter corner 1316.79' east and the Center of Section 10 1316.79' west.

Part C: Field Evidence of Perpetuation or Monumentation of Corner

- | | |
|--|--|
| a. Set 1"IDx28" I.pipe with 4" alum. MDNR cap.
Set measuring nail with MDNR tag in the side of:
5" B.Spruce N05°E 6.4' mrkd "1/16S BT"
6" B.Spruce N34°E 10.2' do
6" B.Spruce S44°E 8.45' do
11" Tamarack N46°W 19.3' do
Set sq'd cedar post adjacent.
E= 7900558.15 N= 161454.24 | b. Set 5/8"x24" rebar with plastic MDNR cap.
Set measuring nail with MDNR tag in the side of:
5" B.Spruce S80°E 18.7' mrkd "1/16S BT"
5" B.Spruce S25°E 36.2 do
16" W.Pine S63°W 18.1' do
4" B.Spruce N64°W 23.1' do
Set sq'd cedar post adjacent.
E= 7900551.30 N= 161051.92 |
|--|--|

Bearings are magnetic. Coordinates are MCS83 in meters, NAD83(2011) Epoch 2010.00 datum.

Stephan J. Szyszkoski

05/30/2018