

LIVINGSTON

# LAND CORNER RECORDATION CERTIFICATE

## FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF--:	LOCATED IN--:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY..... 24 T. 4 N. R. 4 E.		M-8, L-7
2. PROPERTY CONTROLLING IN SECTION....., T. N. S., R. E. W.		
3. MISCELLANEOUS PROPERTY IN SECTION....., T. N. S., R. E. W.		
4. LOT NO. ...., RECORDED PLAT.....		
5. PRIVATE CLAIMS.....		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Donald Bissell, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on October, 1981, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on \_\_\_\_\_, 19\_\_\_\_, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

M-8 Set 4"x 36" concrete monument with aluminum cap midway and on line.      L-7 Set 4"x 36" concrete monument with aluminum cap midway and on line.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

M-8 4"x 36" concrete monument with aluminum cap. S 66° W, 4.52', 16" W. Oak, Spike and Tag S 67° E, 16.12', 20" W. Oak, Spike and Tag N 70° E, 22.76', 22" W. Oak, Spike and Tag N 36° W, 27.49', 12" Cherry, Spike and Tag North, 6.51', 4" Concrete Monument North, 14.5', E-W fence line	L-7 4"x 36" concrete monument with aluminum cap. S 80° E, 30.39', Twin 6" & 7" Ash S 5° E, 26.52', 10" Ash, Spike & Tag N 45° W, 29.03', 4" R. Oak, Spike & Tag N 5° E, 39.37', 8" R. Oak, Spike & Tag All trees blazed.
---	---

SIGNED BY Donald Bissell DATE 12-14-81

SURVEYOR'S MICHIGAN REGISTRATION NO. 18655

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY \_\_\_\_\_ DATE \_\_\_\_\_  
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY \_\_\_\_\_ DATE \_\_\_\_\_  
MICHIGAN REGISTERED LAND SURVEYOR (SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. \_\_\_\_\_