

SURVEY & REMONUMENTATION

FEB 25 1999

SECTION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

FILED

For corners in

LIVINGSTON
 (County)

Located in:

Corner Code #

1. Public Land Survey

T4N R5E

G-12

2. Property Controlling in Section

§ T R

§ T R

3. Miscellaneous

§ T R

Property in Sec.

§ T R

1998 OCT 20 P 1:22

NANCY HAVILAND
 REGISTER OF DEEDS
 LIVINGSTON COUNTY, MI.
 48843

LSC937M

Register of Deeds Stamp & File Number

4. Lot No. _____ Recorded Plat _____

5. Private Claims _____

I, MARY A. BARNWELL, in a field survey on SEPTEMBER 17, 1998, do hereby state that under requirements of D.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A	B	C	D	E	F	G	H	I	J	K	L	M
1												
2	6	5	4	3	2	1						
3												
4	7	8	9	10	11	12						
5												
6	18	17	16	15	14	13						
7												
8	19	20	21	22	23	24						
9												
10	30	29	28	27	26	25						
11												
12	31	32	33	34	35	36						
13												

A. Description of original monument and accessories and/or subsequent restoration:

GLO 1823 SIBLEY SET POST
 WHITE OAK 8 S16E 37 (24.4)
 TAMARACK 16 N50W 85 (56.1)

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

FOUND A "T" IRON SET IN 1969 BY DORCEY OF CONSUMER'S POWER CO. 3 FEET WEST OF THE EASTERLY EDGE OF MACK ROAD (GRAVEL) WITH FENCE TO THE EAST. THIS CORNER POSITION AGREES WELL WITH WITNESSES OF RECORD SINCE 1969.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

G-12 EAST 1/4 CORNER SEC. 33, WEST 1/4 CORNER SEC. 34, T4N, R5E, DEERFIELD TOWNSHIP, LIVINGSTON COUNTY, MICHIGAN;
 RESET FOUND "T" IRON WITH 1 1/4" X 36" BREAKAWAY STEEL PIPE WITH LIVINGSTON COUNTY REMONUMENTATION BRASS CAP WITH SURVEYOR #35999 @ 1/2 FOOT BELOW THE SURFACE OF MACK ROAD.

EAST NAIL WITH LIVINGSTON COUNTY REMON TAG IN SOUTH SIDE 18" MAPLE 16.00'
 S50°E NAIL WITH LIVINGSTON COUNTY REMON TAG IN SOUTH SIDE 10" ASH 31.32'
 S10°E NAIL WITH LIVINGSTON COUNTY REMON TAG IN WEST SIDE 14" HICKORY 30.16'
 N01°E NAIL WITH LIVINGSTON COUNTY REMON TAG IN SE SIDE 24" OAK 35.04'

Signed by [Signature]

Date 10/1/98

Surveyor's Michigan License No. 33971



FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JULY 21, 1988

P.A. 245 1990, APPROVED BY LIVINGSTON COUNTY
 PEER GROUP ON 9-2-98, CO. REP [Signature]

DESIGNED THE MAPS
 DESIGNED THE LEGS
 DESIGNED OCT. 1985