

1999 DEC 29 PM 2:49

*Patricia L. Mackay*  
REGISTER OF DEEDS

SECTION

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in MARQUETTE Located In: \_\_\_\_\_ Corner Code # \_\_\_\_\_  
(County)

- |                                    |                           |            |
|------------------------------------|---------------------------|------------|
| 1. Public Land Survey              | T <u>51N</u> R <u>29W</u> | <u>B-9</u> |
|                                    | T _____ R _____           | _____      |
|                                    | T _____ R _____           | _____      |
|                                    | T _____ R _____           | _____      |
| 2. Property Controlling in Section | S _____ T _____ R _____   | _____      |
|                                    | S _____ T _____ R _____   | _____      |
| 3. Miscellaneous Property in Sec.  | S _____ T _____ R _____   | _____      |
|                                    | S _____ T _____ R _____   | _____      |

LIBER **R2** PAGE **241**

Register of Deeds Stamp & File Number

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_  
5. Private Claims \_\_\_\_\_

I, GERALD W. CARLSON, in a field survey on November 22, 1999, do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

**NOTE:** Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

**A. Description of original monument and accessories and/or subsequent restoration:**

**B-9: Corner common to Sections 19 and 30, T51N-R29W**

1846: Original subdivision survey notes by William Ives' D.S., describe the corner monument as a post referenced by:  
6" Sugar N65W, 28 links 12" Sugar S38E, 07 links

1940: Old Ford Motor Company notes indicate the 6" Sugar, N65W, 28L as found with the diameter being 14".

**B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:**

**B-9: 1999:** Found and established the corner location from the remains of an original bearing tree (6" Sugar, N65W, 28 links) stump that is currently 18" in diameter with evidence of a butt blaze on it. Loggers apparently cut the original B.T. some years ago as the stump is flat cut on top and hollow. The tree was left to lay as it was also hollow. A Ford Motor Company location tag (1959) was on a 9" Hemlock and facing the quarter corner position. I also found the remains of two different squared wood posts in the vicinity and a 28" length of 1/2" water pipe with a tee fitting which was bent over and leaning against the bearing tree log.

Checked line call ( East, 1.77ch, stream, 25L, course-North). The stream (East branch of the Huron river) now appears wider than 25 links. The west bank is vertical and rocky. Taking half of the stream call chainage (12.5 links) to figure west bank comes to 108.57' from the quarter corner to the West bank. Measured 108' from the quarter corner to the West bank.

**C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:**

**B-9: 1999:** Set a 2 3/8" O.D. aluminum pipe capped with a 3 1/4" diameter aluminum tablet (Marquette County Survey Monument) which is stamped to identify the corner. Monument projects 0.50' above ground. Referenced by:

- 9" Hemlock S02W, 9.91' (with Ford Motor Company location tag)
- 5" Ironwood S63W 26.42'
- 12" Hemlock N50W, 36.55'
- 12" Yellow Birch N35E, 24.72'

108' East to the West bank of the East Branch of the Huron River.

Green Steel Sign Post w/ Yellow Survey Marker Sign North, 2.0'

Note: Bearing trees have painted face, butt, and side nail blazes, d.h. measuring nails, and stamped B.T. Tags affixed.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	16		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9	•												
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

**RATIFIED BY PEER GROUP  
P.A. 345 OF 1990**

*Larry J. Bassine*  
DATE 12/27/99



Signed by Gerald W. Carlson

Date 12-22-99

Surveyor's Michigan License No. 24589