

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF--	LOCATED IN--	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY _____	T. _____ N. S., R. _____ E. W.	_____
2. PROPERTY CONTROLLING IN SECTION _____	2 T. 36 N. S., R. 28 E. W.	5, 6, 7
3. MISCELLANEOUS PROPERTY IN SECTION _____	T. _____ N. S., R. _____ E. W.	_____
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

MENOMINEE CO.

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, David B. Babbitt do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above (identified with circles on index code diagram - over) were, in a field survey on March 5, 1976, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____ 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

- 5 - N. 1/16 corner on N-S 1/4 line - not previously marked
- 6 - Center of N.E. 1/4 - not previously marked
- 7 - N 1/16 corner on E. section line. - not previously marked

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

- 5 - Set on line between the N 1/4 corner and the center post of Sec. 2 - Distance proportioned to G.L.O. record.
- 6 - Set at the computed center of the N.E. 1/4 of Section 2
- 7 - Set on line between section corner north and 1/4 corner south and proportioned to G.L.O. record distance.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

- | | | |
|------------------------------|------------------------------|------------------------------|
| 5 - 1" pipe, 4" aluminum cap | 6 - 1" pipe, 4" aluminum cap | 7 - 1" pipe, 4" aluminum cap |
| 4" ironwood - N24°E - 25.0' | 7" W. birch - S45°E - 12.2' | 4" H. Maple - N54°W - 22.2' |
| 6" maple - S75°W - 15.2' | 10" stem of twin maple | 4" H. Maple - S36°E - 11.7' |
| 7" oak - N60°E - 13.9' | N-35°W. 29.0' | |
| | 9" maple - n71°W - 33.9' | |

SIGNED BY _____ DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. _____ (SEAL)

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____

APPROVED AND NOTED BY _____

REGISTERED PROFESSIONAL LAND SURVEYOR

11/1/76