

Montmorency County Remonumentation

Liber 12 Page 08

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

08170
A. PANGAN-MCELROY
RECEIVED
MONTMORENCY CITY
REGISTRY OF DEEDS
DEC 20 10 12 AM '93

For corners in

Montmorency (County) Located In: _____ Corner Code # A-2 ✓
A-3

1. Public Land Survey T 29N R 3E
T 29N R 3E
T _____ R _____
T _____ R _____

2. Property Controlling S _____ T _____ R _____
in Section S _____ T _____ R _____

3. Miscellaneous S _____ T _____ R _____
Property in Sec. S _____ T _____ R _____

4. Lot No. _____ Recorded Plat _____

5. Private Claims _____

APPROVED BY
PEER GROUP

NOV 05 93

Register of Deeds Stamp & File Number

A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1						
3												
4	7	8	9	10	11	12						
5												
6	18	17	16	15	14	13						
7												
8	19	20	21	22	23	24						
9												
10	30	29	28	27	26	25						
11												
12	31	32	33	34	35	36						
13												

I, Donald E. Marlatt, in a field survey on December 10, 19 93, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(A-2) W. ¼ Cor. Sec. 6, T29N, R3E (A-3) S.W. Cor. Sec. 6, T29N, R3E
Post set by Lewis Clason 1839. Post set by Lewis Clason 1839.
Y. Pine 24-S 62 W-26 Y. Pine 18-S 14 W-26
Y. Pine 28-N 45 W-97 Y. Pine 20-N 68 W-30
Survey by D.E. Marlatt 11-5-1976. Y. Pine 25-N 16 E-30
Act 74 D.E. Marlatt L. 1, P. 215. Y. Pine 15-S 51 E-35
M.S.H.D. field notes 1956.
Survey by D.E. Marlatt 11-5-1976.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(A-2) W. ¼ Cor. Sec. 6, T29N, R3E (A-3) S.W. Cor. Sec. 6, T29N, R3E
Fnd. ½" rod & cap #18660. Fnd. conc. Mon.
N 30° E 10.7' 20" Pine stp. N 50° W 67.8' Pine stp. NBT
S 30° E 16.85' 12" Pine stp. S 55° E 33.1' 24" J. Pine NBT
S 30° W 72.1' 12" Oak N 30° E 8.8' 5" J. Pine

No evidence of original corner. No evidence of original corner.

The Peer Group approved (A-2) as a careful and faithful establishment of the position of the corner.
The Peer Group approved (A-3) as the best available evidence of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(A-2) W. ¼ Cor. Sec. 6, T29N, R3E (A-3) S.W. Cor. Sec. 6, T29N, R3E
Set conc. Mon. & Re-Mon cap. Left conc. Mon. & Placed Re-Mon cap.
N 45° E Pine stp. 10.82' S 7° E 12" J. Pine 17.39'
S 32° E Pine stp. 16.91' S 40° E 26" J. Pine 32.9' NBT
S 14° W 4" Maple 23.20' S 60° E 11" J. Pine 30.37'
N 25° W 6" W. Pine 37.7' N 25° E 12" J. Pine 8.95'

Note: Witnesses marked with 30 penny spikes & I.D. tags #18660.

Signed by Donald E. Marlatt Date Dec 15, 1993
Surveyor's Michigan License No. 18660

