

COPY

JUL 14 95 125254

LIBER 15517 PG 422

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970\$ 7.00 MISCELLANEOUS RECORDING

For corners in Oakland (County)

Located In: Oxford Twp. Corner Code #

\$ 2.00 REMONUMENTATION
14 JUL 95 8:39 A.M. RECEIPT# 98
PAID RECORDED - OAKLAND COUNTY
LYNN D. ALLEN, CLERK/REGISTER OF DEEDS

- 1. Public Land Survey T 5N R 10E M-10
2. Property Controlling in Section S T R
3. Miscellaneous Property in Section S T R

Compliance with ACT 345, P.A. 1990

APPROVED ON: 6-21-95 TMS
OAKLAND COUNTY REMONUMENTATION PEER GROUP COMMITTEE
Register of Deeds Stamp & File Number

- 4. Lot No. , Recorded Plat
5. Private Claims

Grid table with columns A-L and rows 1-13. Contains numbers 1-36.

I, Huston K. Kennedy, in a field survey on April 26, 1995, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Professional Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

- A. Description of original monument and accessories and/or subsequent restoration:
1818-GLO Wampler, D.S.; Set Post 12" White Oak N18°W 27 Links; 12" Black Oak S16°E 25 Links
1.) 1977-Kennedy, PS #17623; LCRC L.6821, Pg.466 - Fnd 1" Iron Pipe
2.) 1977-Kennedy, PS #17623; LCRC L.6965, Pg.93 - Fnd 1" Iron, used same wit as 1977 LCRC
3.) 1977-Kennedy, PS #17623; Survey L.7745, Pg.461 - Fnd 1" Iron, used same wit as 1977 LCRC
4.) 1979-Kennedy, PS #17623; Unrecorded Survey - Fnd 1" Iron, used same wit as 1977 LCRC

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:
1995 Kennedy Surveying, Inc. - Kennedy, PS #17623 - Fnd 5/8" Iron Rod on the West side of a old road bed extending North & South wit a tree-rock row extending to the West. The West 1/4 corner of Section 30, T5N, R11E, Addison Twp. (A-10) is located 16.24 feet to the North.

Witnesses from LCRC #1 were used to recover and verify the location of the found 5/8" Iron Rod.

I accepted the found 5/8" Iron Rod as the best evidence of the original corner position.

FIELD MEASUREMENTS BETWEEN

- M-10 to M-11 2656.60 Ft., GLO = 40 chains or 2640.00 Ft.
M-10 to M-9 2480.94 Ft., GLO = 40 chains or 2640.00 Ft.
M-10 to A-10 (Addison Twp.) 16.24 Ft.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:
M-10 I replaced the found 5/8" Iron Rod with a 1/2" Iron Rod encased in a 4" diameter concrete cylinder 36" long w/2" diameter bras cap stamped Oakland County Remonumentation, PS #17623
N63°W 23.82' Set PK & Remon. Washer NE face 18" Hickory
N68°E 32.39' Set PK & Remon. Washer NW face 18" & 19" twin Cherry
N88°E 10.88' Set PK & Remon. Washer North face 10" & 12" twin Hickory
S46°W 7.38' Set PK & Remon. Washer SE face 11" & 19" twin Oak
North 17.08 feet West 1/4 corner Section 30, T5N, R11E, Addison Twp. (A-10)

The selected location is accepted by me and is generally accepted by Professional Surveyors as the best available evidence of position of the original corner.

Signed by [Signature]
Surveyor's Michigan License No. 17623

Date June 15, 1995

