

OTSEGO COUNTY REMONUMENTATION
LAND CORNER RECORDATION CERTIFICATE
 Filing Requirement of Act 74, Mich. PA 1970

For Corners In:

Otsego (County)	Located In	Charlton Twp. North	Corner Code #
1. Public Land Survey	T	31N R 1W	L-5
2. Property Controlling in Section	S	T	R
3. Miscellaneous Property in Section	S	T	R

4. Lot No: _____ Recorded Plat: _____

5. Private Claims: _____

I, Carl T. Kiiskila, in a field survey on June 19, 2013 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

L-5 Corner common to Sections 12&13 T31N, R01W

1850 – GLO – Austin Burt- Set ¼ section post.
 W. Pine 12" S70°W 22
 W. Pine 14" N52°E 37

1978- Unrecorded LCRC Louis J. Czubak- P.S.12581
 Found ½" rod and (2) old posts.
 W. Pine stump and hole S70°W 14.5'
 Stone N74°W 93.0'

1934 – Co. Surveyor Bk. 2, Pg. 248, G.F. DeLaMater
 Found both Govt. B's and P's. OK
 Set ½" bar at corner.
 Large stone N74°W 93'

B. Description of corner evidence found and/or method applies in restoring or re-establishing corner:

L-5 ¼ Corner common to Sections 12&13 T31N, R01W
 Found ½" bar fitting G.F. DeLaMater's survey and the large stone witness listed above. Drove 1" x 3' pipe with DNR aluminum cap over found ½" bar.
 Accepted as a careful and faithful perpetuation of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

L-5 ¼ Corner common to Sections 12&13 T31N, R01W

Set a stamped 4" diameter DNR aluminum cap on 1" x 3' Galvanized pipe.

Wit: N50°E 13.58' to set N&T on W side 7" W. Pine
 S45°E 18.41' to set N&T on SE side 12" R. Pine
 S35°W 28.94' to set N&T on W side 14" W. Pine
 N21°W 15.04' to set N&T on NE side 20" R. Pine
 N64°W 93.0' Large stone

Set blue post 1' North

Signed by: Carl T Kiiskila

Date: 10-14-13

Surveyor's Michigan License No.: 33981

