

9551

SURVEY & REMONUMENTATION

MAY 28 1997

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

COMMISSION

For corners in Roscommon (County)	Located In:	Corner Code #
1. Public Land Survey	T 24N R 2W	G-1
	T R	
	T R	
	T R	
2. Property Controlling in Section	S T R	
	S T R	
3. Miscellaneous Property in Section	S T R	
	S T R	

STATE OF MICHIGAN
ROSCOMMON COUNTY
RECORDED

23 DEC 96 9:47 A.M.

ROBERT W. SMITH
REGISTER OF DEEDS

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

A	B	C	D	E	F	G	H	I	J	K	L	A
2	6	5	4	3	2	1						
3												
4	7	8	9	10	11	12						
5												
6	18	17	16	15	14	13						
7												
8	19	20	21	22	23	24						
9												
10	30	29	28	27	26	25						
11												
12	31	32	33	34	35	36						
13												

I, Marvin E. Myers, P.S., in a field survey on November, 19 96, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Professional Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

GLO-1839 J. Brink Mon- Post Wit- 4" P. Pine N69½°W 13 Lks 6" P. Pine N45°E 34 Lks GLO-1852 W. Burt Mon-Found Post Wit- 6" S. Pine S32°W 81 Lks 6" S. Pine S54°E 200 Lks	L.2, P470 Mon-GLO Mon. Wit-12" Norway N42°W 41.9 18" Norway N28½°E 87.12 14" Norway N23½°W 82.83	L.3, P.33 LCRC M.E. Myers Nov. 1991 Mon- 1/2" Bar in Pav't Box Wit- Face U. Pole N61°E 56.00 Face U. Pole S75°W 71.80 Face U. Pole S40E 39.00 Face U. Pole N52°W 63.50
G.D.Henning (no Date) Mon- Pav't Box	L.588, P.357 F.J.Arleth 12/9/82 Mon- Pav't Box ½" Bar South 33.00	

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found 1" Pipe in Mon Box on line with fence South and the intersection of M-18 E-W and Chase Bridge Road North.
Found ½" Bar South 33.00 feet.

Accepted as the best available evidence of the position of the original corner.

**ROSCOMMON COUNTY
PEER GROUP APPROVAL
DATE NOV 20 1996**

Marvin E. Myers
**Marvin E. Myers, P.S.
County Surveyor**

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Replaced pipe with standard Roscommon County Monument
wit: Nail and tag utility pole N61°E 56.37
Nail and tag utility pole S75°W 72.22
Nail and tag Utility Pole S44°E 39.26
Nail and tag Utility Pole N52°W 67.25



Signed by *Marvin E. Myers* Date Dec 14, 1996
Surveyor's Michigan License No. 31600

LIBER 3 PAGE 342