

DEC 02 1993

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

COMMISSION

For corners in

WAYNE

(County)

Located In:

Corner Code #:

- 1. Public Land Survey T 2S R 9E K-12
2. Property Controlling in Section S T R
3. Miscellaneous Property in Sec. S T R

Compliance with ACT 345, P.A. 1990

APPROVED ON: 11/24/93 TCA
WAYNE COUNTY REMONUMENTATION PEER GROUP COMMITTEE

Register of Deeds Stamp & File Number

RC 1131

- 4. Lot No. Recorded Plat
5. Private Claims

Grid table with columns A-L and rows 2-13. Cell 12,35 contains a black dot.

I, P.P. Palczynski in a field survey on 4 October 1993 do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law, established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

NANKIN TOWNSHIP

G.L.O.- (1830'S) DESCRIPTION OF CORNER MONUMENT NOT STATED IN FIELD NOTES.

WITNESSES LISTED: BEECH 9 N50W 8 (5.3') (GONE) & DO." 10 N49E 20 (13.2') (GONE)

W.P.A.- (1930'S) IRON SET. WITNESSES SHOWN: TEL. POLE NE 79.62' (GONE)
ED. GUY POLE SE 53.50' (GONE)
COR. WINDMILL SW 78.05' (GONE)
ED. POLE NW 48.50' (GONE)

C.S. #261 L.18202 P.570 & 571(9-14-72); C.S.# L.21855 P. 879 & 880 (11-29-83)

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

FOUND 3/4" IRON PIPE IN MONUMENT BOX AT MIDDLEBELT / ANNAPOLIS ROADS.

MEASURED DISTANCES FOR COMPARISON TO W.P.A. RECORDS:

K-12/K13: W.P.A. = 2646.65' MEAS. = 2647.07'
K-12/L-12: W.P.A. = 2625.14' MEAS. = 2625.02'
C.S. = 2624.97' L.18202 P. 570-571.
K-12/K-11: W.P.A. = 2631.99' MEAS. = 2631.83'
K-12/J-12: W.P.A. = 2656' MEAS. = 2654.64'
C.S. = 2654.86' L.21855 P. 879-880



C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

K-12: SECTION CORNER 35 & 36, T2S R9E, FOUND 3/4" IRON PIPE IN MONUMENT BOX. THE SELECTED LOCATION IS ACCEPTED BY THE CONTRACTOR AND IS GENERALLY ACCEPTED BY PROFESSIONAL SURVEYORS AS THE BEST AVAILABLE EVIDENCE OF THE POSITION OF THE ORIGINAL CORNER. PLACED W.C.REMON. BRASS MARKER AND CAP "PPP PS 30096".

SET NAIL/WCR TAG IN SE FACE UTILITY POLE. N50°E 58.61'
FOUND PK NAIL/TAG "KSW/#21584" IN SE FACE UTILITY POLE. N50°E 58.49'
FOUND NAIL/WCRC REF PT TAG IN NE FACE UTILITY POLE. S30°E 90.96'
SET NAIL/WCR TAG IN NW FACE UTILITY POLE. S48°W 61.02'
CENTERLINE FIRE HYDRANT STEM N70°W 97.96'
FOUND CONCRETE MONUMENT. (1' DEEP) N45°W 73.73'

Signed by [Signature] Date 15 NOVEMBER 1993

Surveyor's Michigan License No. 30096

Handwritten initials: 2R 11KD