

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

L129358 PA 6-40

For corners in

WAYNE
(County)

Located In:

Corner Code #

- | | | | |
|------------------------------------|--------------|--------------|------------------------|
| 1. Public Land Survey | T <u>2</u> S | R <u>9</u> E | <u>M-8</u> |
| | T _____ | R _____ | <u>INKSTER</u> |
| | T _____ | R _____ | <u>NANKIN TOWNSHIP</u> |
| | T _____ | R _____ | _____ |
| 2. Property Controlling in Section | S _____ | T _____ | R _____ |
| | S _____ | T _____ | R _____ |
| 3. Miscellaneous Property in Sec. | S _____ | T _____ | R _____ |
| | S _____ | T _____ | R _____ |

Compliance with
ACT 345, P.A. 1990 *J.P.J.*

APPROVED ON: DEC. 18, 1996
WAYNE COUNTY REMONUMENTATION
PEER GROUP COMMITTEE
 Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
 5. Private Claims _____

I, PETER P. PALCZYNSKI in a field survey on 13 DECEMBER, 1996, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

1816 G.L.O. - SET POST SUG 12" N80°E 13 LKS.
 JOSEPH FLETCHER W. O. 20" S62°W 25 LKS.

SEE BACK OF THIS SHEET (NEXT PAGE)
 FOR CONTINUATION OF SECTION "A"

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

FOUND 3/8" IRON IN MONUMENT BOX, AT CENTERLINE INTERSECTION OF AVONDALE AVE. & INKSTER ROAD ASPHALT PAVEMENT. SET GRAY "WAYNE COUNTY REMONUMENTATION" CAP ON 3/8" IRON.

MEASURED:
 M-7/M-8/B-8 = 90°30'09"
 B-8/M-8/M-9 = 89°48'22"
 M-9/M-8/L-8 = 90°10'05"
 L-8/M-8/M-7 = 89°31'24"

M-8 IN T2S, R9E, IS THE SAME CORNER AS A-8, T2S, R10E.

CORNER POSITION VERIFIED USING 2 WITNESSES AND COMPARISONS TO RECORD INFORMATION FROM SECTION "A".

MEASURED:
 M-8 / M-7 = 2648.83' (R=2648.40/2648.44)
 M-8 / B-8 = 2651.55' (R=2651.69)
 M-8 / M-9 = 2647.48' (R=2647.26/2647.50)
 M-8 / L-8 = 2667.69' (R=2665.84)

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

M-8 T2S, R9E & A-8, T2S, R10E,
 FOUND 3/8" IRON IN MONUMENT BOX, AT CENTERLINE INTERSECTION OF AVONDALE AVE. & INKSTER ROAD ASPHALT PAVEMENT. SET GRAY "WAYNE COUNTY REMONUMENTATION" CAP ON 3/8" IRON.

FOUND PK NAIL/WCRC REF PT WASHER IN SE FACE UTILITY POLE	N44°E	52.87'
CENTERLINE FIRE HYDRANT STEM	S76°E	123.86'
FOUND PK NAIL/WCRC REF PT WASHER IN SW FACE UTILITY POLE	S39°E	61.15'
SET NAIL/WCRC TAG IN SOUTHWEST FACE OF UTILITY POLE	S73°W	57.97'
CENTERLINE FIRE HYDRANT STEM	S50°W	50.76'
FOUND CONCRETE MONUMENT	N59°W	70.48'
FOUND PK NAIL/WCRC REF PT WASHER IN SW FACE UTILITY POLE	N58°W	51.85'

SELECTED LOCATION IS ACCEPTED BY THE CONTRACTOR AND IS GENERALLY ACCEPTED BY PROFESSIONAL SURVEYORS AS THE BEST AVAILABLE EVIDENCE OF THE POSITION OF THE ORIGINAL CORNER.

Signed by *P.P.P.* Date 23 DEC 96

Surveyor's Michigan License No. 30096
 2S9EM-8.DOC

	A	B	C	D	E	F	G	H	I	J	K	L
2	6		5		4		3		2			
3												
4	7		8		9		10		11			
5												
6	18		17		16		15		14			
7												
8	19		20		21		22		23			
9												
10	30		29		28		27		26			
11												
12	31		32		33		34		35			
13												

\$ 10.00 DEED
 26 DEC 96 8:22 A.M. RECEIPT# 1B
 RECORDED
 FOREST E. YOUNGBLOOD, REGISTER OF DEEDS
 WAYNE COUNTY, MI
 \$ 4.00 REMONUMENTATION



1996 WAYNE COUNTY REMONUMENTATION PROGRAM

Continuation of Section "A"

History compiled by:
Peter P. Palczynski, P.S. #30096
AMBIT LAND SURVEYORS, INC.

M-8 (E. 1/4 CORNER OF SECTION 24 & W. 1/4 CORNER OF SECTION 19, T2S, R10E, A-8)

DATE	COMPANY SURVEYOR JOB #	P.S. #	P.A. 74 L.C.R.C.	LOCATION OF SURVEY	MONUMENT DESCRIPTION	WITNESSES	BEARING & DISTANCE	ID #	COMMENT
1816	G.L.O. JOSEPH FLETCHER			SET POST.	SUG. 12' W.O. 20'		N80°E 13 LKS S62°W 25 LKS.		NOTES = 40.00 CHAINS
1930'S	W.P.A.			IRON (E-24 #104 FOR NANKIN TOWNSHIP T2S, R9E)	CROSS ON SIGN POST ED GUY POLE BASE OF FIRE HYD ED POLE		NE 34.65' SE 62.32' SW 66.90' NW 54.08'	1 2 3 4	GONE GONE GONE GONE
2/22/73	WARNER, CANTRELL & PADMOS, INC. TERENCE B. CANTRELL, RLS	#5782	C.S. 768 C.S. 766	N.E. 1/4 SECTION 24	IRON (W-19 # 92 FOR DEARBORN TOWNSHIP T2S, R10E)	CROSS ON SIGN POST ED GUY POLE BASE OF FIRE HYD ED POLE	NE 34.65' SE 62.32' SW 66.90' NW 54.08'	1 2 3 4	GONE GONE GONE GONE

W.P.A. RECORD:

- M-8/M-7 = 2648.40 / 2648.44'
- M-8/M-9 = 2647.26' / 2647.50'
- M-8/B-8 = 2651.69'
- M-8/L-8 = 2665.84'
- M-7/M-8/B-8 = 90° 27' 10"
- B-8/M-8/M-9 = 89° 51' 20"
- M-9/M-8/L-8 = 90° 11' 10"
- L-8/M-8/M-7 = 89° 30' 00"

LI29358PA641