

**SURVEY & REMONUMENTATION**

MAR 09 1998

SECTION

**LAND CORNER RECORDATION CERTIFICATE**  
Filing Requirement of Act 74, Mich. P.A. 1970

RECORDED  
WASHTENAW COUNTY, MI

JAN 22 8 30 AM '98

PEGGY A. HAINES  
COUNTY CLERK/REGISTER

For corners in

Washtenaw - (county)	Located In	Corner Code #
1. Public Land Survey	T <u>4S</u> R <u>5E</u>	<u>J-9</u>
	T _____ R _____	_____
	T _____ R _____	_____
	T _____ R _____	_____
2. Property Controlling in Section	S _____ T _____ R _____	_____
	S _____ T _____ R _____	_____
3. Miscellaneous Property in Sec.	S _____ T _____ R _____	_____
	S _____ T _____ R _____	_____
4. Lot No. _____, Recorded Plat _____		
5. Private Claims _____		

- COPY -

- COPY -

Liber **00002** Page **0022** *RM*  
Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

I, R. Timothy Tietsema, in a field survey on 16 April, 1997, do hereby certify that under the requirements of P.A.74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with the regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management of by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4, and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered. found as expressed below.

**NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.**

**A. Description of original monument and accessories and/or subsequent restoration:**

Date	Name	Notes	Set Original Corner	Monument	Dimensions	Remarks
7/30/1819	GLO	Fld. Notes	Set Original Corner	1) 8" Lynn 2) 8" Lynn	N82E 17 links (11.22') N78W 21 links (13.86')	Set Post for 1/4 Corner between Sec. 23 & 26
6/21/1938	W.J. Armstrong A.A. Wistert R.R. Graf	Grid Book	Fnd. Stake & Stones	3) 6" Elm 4) 10" Walnut 5) 15" Walnut 6) 8" Walnut 7) 14" Walnut	N58E 44.3' N77E 101.2' N66W 66.5' N49W 39.6' N12W 32.7'	Reset with 1-1/2"x36" Iron Pipe
6/3/1968	Washtenaw Engineering JOB NOS: 2528, 2585, & 2646	Boundary	Fnd. Iron Pipe			
9/24/1968	Washtenaw Engineering JOB NO: 3087	Boundary	Fnd. Iron Pipe			
11/30/1968	Washtenaw Engineering JOB NO: 3302	Boundary	Fnd. Iron Pipe			
3/30/1973	Glenn Richard 13040	LCRC L.3 P.139	Fnd. 1-1/2" Iron Pipe	6) 14" Walnut 7) 26" Walnut 8) 2" Steel post in concrete 9) 3" Steel post in concrete	N50W 39.75' to nail N10W 32.82' to nail N05W 26.5' South 26.8'	
4/27/1987	Allen Rentschler 15411	Boundary	Fnd. 1-1/2" Iron Pipe	4) 21" Walnut 5) 24" Walnut 6) 16" Walnut 7) 26" Walnut	N77E 101.2' N66W 66.5' N49W 39.6' N12W 32.7'	

**B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:**

In April of 1997 LSC found a 1 1/2" Iron Pipe from three previous witnesses (6, 7, & 8) and added one additional witness (10).

**C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:**

Found 1 1/2" Iron Pipe, Reset with a 1" Iron Pipe and Remonumentation Cap.  
 6) 15" Walnut N50W 39.64 to P.K. & r/t Fence line running  
 7) 24" Walnut N10W 32.81 to P.K. & r/t Nly & Sly  
 8) 2" Steel post North 26.45'  
 10) 3" Steel post South 29.62'

**APPROVED**  
DATE 12/2/97  
CO. REP. [Signature]

It is our opinion that this corner represents the original corner and is accepted as a permanent and faithful perpetuation of the position of the original corner.

Signed by [Signature]  
Surveyor's Michigan License No. 20712

Date 2 December 1997

