

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Alger (County)	Located In:	Corner Code #
1. Public Land Survey	T R	
	T R	
	T R	
2. Property Controlling in Section	S 2 T 47N R 17W	16
	S 2 T 47N R 17W	14
	T R	
3. Miscellaneous Property in Sec.	S T R	
	S T R	
4. Lot No. , Recorded Plat		
5. Private Claims		

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3										2			
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

I, Stephan J. Szyszkoski, in a field survey on 07/03/13 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey Instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(16-Sec. 2) East 1/16 corner between Sections 2 and 11. Not previously monumented.

(14-Sec. 2) South 1/16 corner between Sections 1 and 2. Not previously monumented.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(16-Sec. 2) Established the position for the corner midway and on the Section line between Section corner 1321.72' east and Quarter corner 1321.72' west.

(14-Sec. 2) Established the position for the corner midway and on the Section line between Section corner 1313.35' south and Quarter corner 1313.35' north.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(16) Set 1"IDx36" I.pipe with 4" alum. MDNR cap.  
Set measuring nail with MDNR tag in the side of:  
11" Sugar S89°W 25.5' mrkd "E1/16 BT"  
8" Sugar N10°W 35.25' do  
11" Sugar N30°E 40.5' do  
14" Sugar S70°E 14.9' do  
E= 8046742.528 N= 190051.576

(14) Set 1"IDx36" I.pipe with 4" alum. MDNR cap.  
Set measuring nail with MDNR tag in the side of:  
8" Maple S45°W 7.5' mrkd "S1/16 BT"  
8" Maple S22°E 14.4' do  
10" Maple N55°E 16.3' do  
12" Cherry N62°W 27.7' do  
E= 8047141.538 N= 190453.143

Bearings are magnetic. Coordinates are MCS83 in meters (NAD83(2011) Datum).  
Coord. Ref.=NGS PID DJ8902: N= 177197.949 m. E= 8027768.701 m.

Signed by Stephan J. Szyszkoski  
Surveyor's Michigan License No. 33986

Date 08/29/2013

For the Michigan Department of Natural Resources, Forest Resources Division

