

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Alger

(County)

Located In:

Corner Code #

1. Public Land Survey

T R
T R
T R

2. Property Controlling
in Section

S 27 T 49N R 13W 2
S 27 T 49N R 13W 6

3. Miscellaneous
Property in Sec.

S T R
S T R

4. Lot No. , Recorded Plat

5. Private Claims

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

I, Stephan J. Szyszkoski, in a field survey on 03/19/2012 do hereby state

that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(2-Sec. 27) East 1/16 corner between Sections 22 and 27. Not previously monumented.

(6-Sec. 27) Northeast 1/16 corner, Section 27. Not previously monumented.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(2-Sec. 27) Established the position for the corner midway and on the Section line between Quarter corner 1313.02' west and Section corner 1313.02' east.

(6-Sec. 27) Established the position for the corner at the intersection of straight lines connecting opposite 1/16 corners.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(2) Set 1"IDx36" I.pipe with 4" alum. MDNR Cap.
Set measuring nail with MDNR tag in the side of:
7" Cherry N56E 16.85' mrkd "E1/16 BT"
6" W.Pine S57E 62.35' do
30" Sugar S39W 43.95' do
10" Maple N86W 61.4' do
Bearings are magnetic.

(6) Set 1"IDx36" I.pipe with 4" alum. MDNR cap.
Set measuring nail with MDNR tag in the side of:
8" W.Pine South 21.9' mrkd "NE1/16 BT"
14" W.Pine S46W 21.5' do
7" Cherry N68W 11.45' do
6" W.Spruce N36E 9.7' do
Bearings are magnetic.

Signed by Stephan J. Szyszkoski
Surveyor's Michigan License No. 33986

Date 05/22/2012

For the Michigan Department of Natural Resources, Forest Resources Division



47519

47520