

MAR 07 2000

ALLEGAN COUNTY REMONUMENTATION

LAND CORNER RECORDATION CERTIFICATE

SECTION

Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

ALLEGAN COUNTY..... Located in: ..LEE..... Township
Corner Code #

- Public Land Survey T.1 N.. R.15 W.H-8.....
T..... R..... CENTER, SEC. 22
- Property Controlling S..... T..... R.....
in Section S..... T..... R.....
- Miscellaneous S..... T..... R.....
Property in Sec. S..... T..... R.....
- Lot No., Recorded Plat
- Private Claims.....

Register of Deeds Stamp & File Number

I, **George J. Mitchell**....., in a field survey on ...**September 29, 1999**.....
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner
points mentioned in lines 1 and 2 above were in conformance with regulations and rules
therefore as required in the current manual of survey instructions of the United States
Department of the Interior, Bureau of Land Management or by decree of a Court of Law
and/or that the corner points mentioned in lines 3, 4, and 5 above were in conformance
with the rules of the Michigan Board of Land Surveyors or by decree of a Court of Law;
established, re-established, monumented, re-monumented, recovered, found as expressed
below:

A. Description of original monument and accessories and/or subsequent restoration:

H-8

SEE SHEET 2 OF 2 FOR CORNER HISTORY

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

FOUND 1/2 PIPE FROM ITEMS 2 THROUGH 5 OF CORNER HISTORY. THE FOUND CORNER IS ON THE
NORTH-SOUTH QUARTER LINE AND 0.63' NORTH OF EAST-WEST QUARTER LINE

SET ALLEGAN COUNTY STANDARD 3/4" BY 36" IRON PIN WITH REMON CAP IN MON BOX

THIS POSITION NOT ESTABLISHED BY ORIGINAL GOVERNMENT SURVEYORS. THIS MONUMENT IS ACCEPTED
AS THE BEST AVAILABLE EVIDENCE OF THE POSITION OF THE CORNER.

THIS CORNER WAS APPROVED BY THE ALLEGAN COUNTY SURVEYORS PEER GROUP ON OCTOBER 12, 1999

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

CENTER OF SECTION 22, TOWN 1 NORTH, RANGE 15 WEST

A.C. REMON TAG & NAIL IN NORTH SIDE OF 16" POPLAR
A.C. REMON TAG & NAIL IN NORTHWEST SIDE OF 16" POPLAR
A.C. REMON TAG & NAIL IN NORTHWEST SIDE OF 8" MAPLE
A.C. REMON TAG & NAIL IN NORTHEAST SIDE OF 30" OAK
CENTER OF N-S ASPHALT ROAD WEST
H-8 TO H-7 MEASURED 2613.26 FEET
H-8 TO G-8 MEASURED 2615.05 FEET
H-8 TO H-9 MEASURED 2630.73 FEET
H-8 TO I-8 MEASURED 2607.86 FEET

AZ. 085° 36.97 FEET
AZ. 033° 56.00 FEET
AZ. 245° 104.67 FEET
AZ. 320° 112.22 FEET
2'

APPROVED REMONUMENTATION CORNER
P.A. 345 OF 1990
ALLEGAN COUNTY

DATE APPROVED OCT. 12, 1999
COUNTY REP. [Signature]

Signed by

Date

Surveyor's Michigan License No. 19618

SHEET 1 OF 2



RE SURVEY &
SECTION

MAR 07 2000

SECTION

GOVERNMENT CORNER HISTORY

CENTER OF SECTION 22
TOWN 1 NORTH, RANGE 15 WEST

H-8

NOT SET IN ORIGINAL GOVERNMENT SURVEY

- | | | |
|----|---------------------------------|---|
| 1. | OLD NOTES NO DATE
MACDOUGHAL | STAKE
MAPLE SW 85.4'
PINE SE 7.1'
2615' NORTH TO N1/4 POST
2635' SOUTH TO S1/4 POST
2615' EAST TO E1/4 POST
2614' WEST TO W1/4 POST |
| 2. | D. RATEKIN P.S. 1970 | FD 1/2" PIPE
2613.66 NORTH TO N1/4 POST |
| 3. | D. RATEKIN P.S. 1973 | L.C.R.C. L. 002 P. 028
FD 1/2" PIPE
14" POPLAR N45E 36.24'
6" POPLAR S85E 15.1'
12" POPLAR N15E 36.3'
18" POPLAR N15W 50.35'
ST. SIGN S15E 21.65' |
| 4. | D. RATEKIN P.S. 1974
1976 | SAME AS ABOVE |
| 5. | G. MITCHELL P.S. 1999 | FD 1/2" PIPE |