

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in
ALLEGAN

(County)

Located In:

Corner Code \neq

1. Public Land Survey T 1N R 15W L3
T R
T R
T R
2. Property Controlling S 1 T 1N R 15W 16
in Section S 1 T 1N R 15W 12
3. Miscellaneous S T R
Property in Sec. S T R

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat
5. Private Claims

I, GARY C. BILOW, in a field survey on April 10, 1991, 19 , do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

A. Description of original monument and accessories and/or subsequent restoration:

- (L-3) ORIGINAL CORNER POST ESTABLISHED BY U.S. GOVERNMENT DEPUTY SURVEYOR C. BRITIAN, 1831. ACCESSORIES: PINE 15 N23E 88, PINE 12 S31E 70. CORNER SHOWN IN PERSONAL RECORD OF FORMER ALLEGAN COUNTY SURVEYOR HUGH MacDOUGALL (ca.1900) AS "STAKE". NO ACCESSORIES NOTED. DISTANCES SHOWN TO K-3 AND M-3 ARE BOTH 2650'.
- (16) CORNER NOT ESTABLISHED IN ORIGINAL SURVEY. CORNER SHOWN IN PERSONAL RECORD OF FORMER ALLEGAN COUNTY SURVEYOR HUGH MacDOUGALL (ca.1900) AS "STAKE" MIDWAY BETWEEN M-3 AND L-3. NO ACCESSORIES ARE NOTED.
- (12) CORNER NOT ESTABLISHED IN ORIGINAL SURVEY. FOUND NO RECORD OF SUBSEQUENT MONUMENTATION.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

- (L-3) ORIGINAL POST AND ACCESSORIES NOT RECOVERED. MacDOUGALL'S STAKE NOT RECOVERED. FOUND CORNER MONUMENTED BY A 1 1/2" PIPE RAISED TO SURFACE WITH 1/2" PIPE AND SET AMONGST PIECES OF STONE AND BRICK, 2.8' WEST AND 5.4' NORTH OF THE PROPORTIONATE POSITION. ACCEPTED SAME AS THE BEST AVAILABLE EVIDENCE OF THE ORIGINAL CORNER LOCATION AND REPLACED PIPES WITH A 1/2"x36" REBAR ENCASED IN A 4" DIAMETER CONCRETE CYLINDER CAPPED WITH A CAST ALUMINUM MICHIGAN DEPARTMENT OF NATURAL RESOURCES TABLET 6" BELOW GRAVEL ROAD SURFACE.
- (16) FOUND NO MONUMENTATION AT THIS POSITION. REESTABLISHED CORNER MIDWAY AND ON A STRAIGHT LINE BETWEEN M-3 AND L-3 AS RECORDED THIS DATE. MONUMENTED THE CORNER POSITION WITH A 1/2"x18" REBAR CAPPED WITH A YELLOW PLASTIC CAP STAMPED "G.C. BILOW LLS 26453", 6" BELOW GRAVEL ROAD SURFACE.
- (12) ESTABLISHED CORNER MIDWAY AND ON A STRAIGHT LINE BETWEEN L-2 AND L-3 AS RECORDED THIS DATE. MONUMENTED THE CORNER POSITION WITH A 1/2"x18" REBAR WITH YELLOW PLASTIC CAP STAMPED "G.C. BILOW LLS 26453", 6" BELOW GRAVEL ROAD SURFACE.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

- L-3 SET CONCRETE MONUMENT WITH MDNR CAP N60W 42.49' SET NAIL AND MDNR TAG IN WEST FACE OF WEST BOLE OF 27" TWIN OAK; S62E 89.86' SET NAIL AND MDNR TAG IN SOUTH ARM OF SOUTH BOLE OF 12" AND 18" TWIN OAK; S35W 51.62' SET NAIL AND MDNR TAG IN SOUTH FACE 10" PINE; N52E 92.55' SET NAIL AND MDNR TAG IN SOUTH FACE 9" PINE.
- (16) SET 1/2" REBAR WITH CAP #26453 N01E 28.21' SET NAIL AND MDNR TAG IN EAST FACE POWER POLE; S55E 33.87' SET NAIL AND MDNR TAG IN NE FACE 10" OAK; S74W 57.40' SET NAIL AND MDNR TAG IN NORTH FACE 32" OAK; SOUTH 32.72' FOUND 1/2" IRON BAR WITH CAP #19610; NORTH 33.00' SET 4" DIA. CONCRETE MONUMENT WITH ALUMINUM MDNR TABLET.
- (12) SET 1/2" REBAR WITH CAP #26453 N86W 33.49' SET NAIL AND MDNR TAG IN SOUTH FACE 18" OAK; N82E 49.36' SET NAIL AND MDNR TAG IN SOUTH FACE 26" OAK; S63E 45.89' SET NAIL AND MDNR TAG IN NORTH FACE 14" OAK; S52W 38.60' SET NAIL AND MDNR TAG IN SE FACE 14" OAK; WEST 2' CENTERLINE OF GRAVEL SURFACE.

Signed by Gary C. Bilow Date 8/11/91

Surveyor's Michigan License No. 26453

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN 1971
REVISED MAY 1975
REVISED JAN 1983

