

REMONUMENTATION

APR 07 1998

SECTION

ALLEGAN COUNTY REMONUMENTATION LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

<u>Allegan</u>	Located in:	Corner Code #
(County)	Wayland Township	
1. Public Land Survey	T3N R 11W	✓ K-1
	T R	
	T R	
	T R	
2. Property Controlling	S T R	
in Section	S T R	
3. Miscellaneous	S T R	
Property in Sec.	S T R	

98 JAN 21 PM 1:38
REGISTER OF DEEDS
ALLEGAN COUNTY, MICH.

FILED

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

I, Robert Jonker, in a field survey on Jan. 6, 1997 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A	B	C	D	E	F	G	H	I	J	K	L	M
1												
2	6	5	4	3	2	1						
3												
4	7	8	9	10	11	12						
5												
6	18	17	16	15	14	13						
7												
8	19	20	21	22	23	24						
9												
10	30	29	28	27	26	25						
11												
12	31	32	33	34	35	36						
13												

A. Description of original monument and accessories and/or subsequent restoration:

1831 Sylvester Sibley D.S.
77.39, Intersect N line 27 ~~11~~ Nks West of post for which
Tamarack 7 is the corner true

Exxel Eng. No date
JHD capped iron
Spk S'ly side 10" Ash N70°E 17.58'
Spk S'ly side 16" W. Ch. N70°W 13.2'
Spk S'ly side 20" Elm? SW 29.46'
C/L gravel road SE 35'±

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:


Found John Dillingham capped iron 17.82' West of Leighton corner by
Exxel wit. listed in "A" above. Jog distance checks to Leighton corner
as set by Ratekin.

Accepted as a careful and faithful perpetuation of
the position of the original corner.

Peer group approved April 8, 1997.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Replaced with std. Allegan County capped monument.
Leighton Twp. corner East 17.82'
Found Spike on SE side 10" Ash N 70° E 17.57'
Found spike on SW side 14" Cherry N 60° W 13.18'
Found spike on NW side 16" Elm S 45° W 29.4'



APPROVED REMONUMENTATION CORNER
P.A. 345 OF 1990
ALLEGAN COUNTY
DATE APPROVED 4-8-97
COUNTY REP. K.V.O.

Signed by Robert J. Jonker
Surveyor's Michigan License No. 21572

Date 4-4-97

USER:0006PAGE258