

Allegan County Remonumentation
LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in
Allegan Co.
(County)

Located In: Hopkins Corner Code #
Twp.

**SURVEY &
REMONUMENTATION**

APR 29 1996

COMMISSION

1. Public Land Survey

T 3N R 12W B-1

2. Property Controlling
in Section

S T R

3. Miscellaneous
Property in Sec.

S T R

4. Lot No. , Recorded Plat

5. Private Claims

1995 DEC 14 PM 2:33
FILED

Register of Deeds Stamp & File Number

I, Robert J. Jonker, in a field survey on December 13, 19 94,
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned
in lines 1 and 2 above were in conformance with regulations and rules theretofore as required in the
current manual of survey instructions of the United States Department of the Interior, Bureau of Land
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a
Court of Law; established, re-established, monumented, re-monumented, recovered, found as
expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

Not set in G.L.O. survey
No road commission witnesses

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

B-2, Set corner on Twp. line, prorating the East-West distance to the G.L.O.
distance between the NW and NE corners of Section 6.

NW cor. section, West 2598.39'
NE cor. section, East 2651.42'
Center of section, South 2411.84'

APPROVED REMONUMENTATION CORNER
P.A. 345 OF 1990
ALLEGAN COUNTY
DATE APPROVED 12-14-95
COUNTY REP. Robert J. Jonker

This position is accepted by myself as a careful determination of the position
of the corner.

Peer group approved on 12-14-95.
C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Set 3/4" x 36" standard capped Allegan County monument on twp. line and on
C/L E-W gravel road.

A/C tag on W. side P. pole	N 15° W 60.20'
A/C tag on S. side 10" W. Cherry	S 60° W 105.5'
A/C tag on S. side 8" Sas.	S 10° W 58.43'
SW cor. garage (brick)	N 30° E 101.93'
S 1/2 Cor. Sec. 31, T4N, R12W	West 18.06'
C/L top. S. gas valve.	S 50° E 77.45'

Signed by Robert J. Jonker
JONKER LAND SURVEYS, P.C. 21572

Date December 14, 1994

Surveyor's Michigan License No. 21572

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 29, 1971
REVISED MAY 14, 1975
REVISED JAN., 1983

0005 PAGE 223