APR 2 5 1995

For corners in Allegan

(County)

1. Public Land Survey

Allegan County Remonumentation LAND CORNER RECORDATION CERTIFICATE COMMISSION

Filing Requirement of Act 74, Mich. P.A. 1970			Co a	1994	
Located In: Hopkins Twp	Corner Code ≠		TESTS II	330 t	TI ==
. T <u>3N</u> R 12W	B-3	ļ		<u>6</u>	
T R			12 V	<u> </u>	[1]
TR		}	SS	Ģ	U
T B			E. \$		
_ ' '		·	(E	1 5	

		TR			S:32	20	<u>ب</u>			U	
2.	Property Controlling	\$ T R		1	×.	12.	ង				
	in Section	S R		Ţ.							
	Miscellaneous	S T R		Registe	er of Deec	is Stan	որ & ք	ile N	umi)er	
.	Property in Sec.	S R									_
		Recorded Plat			A R C	D E	F G	н і	J	ĸ	ι
		necolded Flat				1		\Box		7	٦
5.	Private Claims				-6-	å—↓—.	4	· 5 —	2-		-{

Robert Jonker , in a field survey on August 20 94

do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in tines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 and 1 a above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

> Jonker, LCRC#3-349 1982, Jonker, LCRC#3-349 Fd. "T" iron per wit. of L.847,P.61

A. Description of original monument and accessories and/or subsequent restoration: GLO - post, Beech 18", S 15° E 5 Pine 36", N 37° E 7 J.W. Hicks, Co.Surveyor, May 1,1876 stake & 2 stones

L.947,P.61. "T" iron, Sandel 1978 (set) 36" tree S 1° E 44.66' 6" Tw. Sas. S 45° W 27.99' 5" Sas. S 45° E 27.43'

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner: Found "T" iron per wit. listed in A above in 1978 & 1982.

Accepted as a careful and faithful perpetuation of the position of the original corner.

APPROVED REMONUMENTATION CORNER P.A. 345 OF 1990 ALLEGAN COUNTY DATE APPROVED: 19-16-9

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Replaced "T" iron with 36" standard Allegan County monument.

A.C. Tag E. side 36" Ash Az. 183° A.C. Tag on top 10" stump Az. 230° A.C. Tag SW side 6" Sas. Az. 145° A.C. Tag on top 11" stump Az. 120° 44.53 33.48' 50.99

JONKER SURVEYOR NO. 21572 CO LAND SUN

NI OF MICHIGA

ROBERT J.

Signed by Robert J. Oorker Date Date Date Date Date Date Date Date	e <u>October 11, 1994</u>
Signed by JONKER LAND SURVEYS, P.C. 21572 Surveyor's Michigan License No. 21572	FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971 REVISED MAY 14, 1975
	REVISED JAN., 1983

UBER 0005 PAGE 021