

## REMONUMENTATION

APR 25 1995

## COMMISSION

Allegan County Remonumentation  
 LAND CORNER RECORDATION CERTIFICATE  
 Filing Requirement of Act 74, Mich. P.A. 1970

For corners in  
 Allegan  
 (County)

Located In:  
 Hopkins Twp.

Corner Code #

1. Public Land Survey

T3N R 12W

C-2

T R

T R

T R

2. Property Controlling in Section

S T R

S T R

3. Miscellaneous Property in Sec.

S T R

S T R

4. Lot No. , Recorded Plat

5. Private Claims

1994 DEC 16 AM 9:56  
 REGISTER OF DEEDS  
 ALLEGAN COUNTY, MICH.

FILED

Register of Deeds Stamp &amp; File Number

I, Robert Jonker, in a field survey on August 20, 19 94

do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law, established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

## A. Description of original monument and accessories and/or subsequent restoration:

GLO survey - set  $\frac{1}{4}$  sec. post

Beech 14" S 42° E 6'

Beech 10" S 53° W 19'

Co. Surveyor-J.W. Hicks, 1876

Iron - 2 feet

Russ Donker - Iron 1972

24" Ash North 28.2'

12" Maple WSW 70.9'

Fc. post SSE 32.0'

Don Sandell, 1978, Rd. 3/4" Iron

12" Maple N 28° W 70.07' stump

Guard rail post N 27° E 59.41'

Guard rail post S 23° E 62.55'

Conc. project marker S 68° W 64.6' (over)

## B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found  $\frac{1}{2}$ " capped rerod @ grade in top of 1" x 13" pipe, 8" below grade per wit. of 1978, conc. project marker; and Ratekin wit. of 1979, road 10' East. and per wit. of L.C.R.C. in Liber 3 on Page 349.

Accepted as a careful and faithful perpetuation of the position of the original corner.

APPROVED REMONUMENTATION CORNER

P.A. 345 OF 1990

ALLEGAN COUNTY

DATE APPROVED 11-8-94COUNTY REP. R.V.C.

## C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Replaced with standard 24" capped Allegan County monument.

A.C. Tag NW side p.pole Az. 60° 70.24'

A.C. Tag Top guard post Az. 100° 79.78'


A.C. Tag Top cor fc post Az. 150° 59.12'

SE rod in top of conc triangular r/w marker Az. 250° 64.48'

C/L top M.B.T. ped. Az. 330° 32.4'

on C/L E-W roads

C/L N-S pav't is 9" East

Signed by Robert J. JonkerDate October 14, 1994Surveyor's Michigan License No. 21572

USE 0005 PAGE 063

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971  
 REVISED MAY 14, 1975  
 REVISED JAN., 1983

Sheet 1 of 2

*Allegm*

Section "A." continued

Ratekin, 1979, Reset Iron

14" Maple NW 54.3'

24" Sycamore NE 91.5'

14" Sycamore SW 100.0'

Gas vent SE 83.3'

C/L N-S road 10' East

L.C.R.C. - Liber 3, Page 349, Jonker 1982 (found capped Ratekin iron)

PK on SE side guard post N 45° E 42.55'

PK on NE side guard post S 50° E 48.26'

C/L R.O.W. post S 68° W 64.6'

C/L "X" 10' E m/1