

Allegan County Remonumentation
LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in
Allegan
(County)

Located in:

Corner Code #

1. Public Land Survey

T 3N R 12W

H-1 (N1, 3)

T _____ R _____

Hopkins Twp.

T _____ R _____

T _____ R _____

2. Property Controlling
in Section

S _____ T _____ R _____

S _____ T _____ R _____

3. Miscellaneous
Property in Sec.

S _____ T _____ R _____

S _____ T _____ R _____

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____

5. Private Claims _____

I, John C. Bueche, in a field survey on October 1, 19 96,
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the
current manual of survey instructions of the United States Department of the Interior, Bureau of Land
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a
Court of Law; established, re-established, monumented, re-monumented, recovered, found as
expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

H-1 Not set by GLO

No other information


B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

H-1 Set cor. 1/2 the distance between NW cor. sec. 3 & NE cor. sec. 3
on line SW cor. 34 & SE cor. 34, T4N, R12W
5272.74' (2636.37' - 2636.37')
No field divisions South
This position not established by original government surveyors.
This monument is accepted as the best available evidence of the
position of the corner.
Approved by Allegan Co. Peer Group 5/14/96

APPROVED REMONUMENTATION CORNER
P.A. 345 OF 1990
ALLEGAN COUNTY
DATE APPROVED 5-14-96
COUNTY REP. Rich L. Van Orden

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

H-1 Set Allegan Co. Mon. 3/4" x 24" Pin with Cap
Nail & Allegan Co. Remon. Tag in E side PP N 24 W 73.60'
X" cut on top CMP (E. Culvert) N 82 W 77.90'
X" cut on top CMP (E. Culvert) S 79 W 89.05'
SE cor. small bldg. N 14 W 96.75'
Allegan Co. Mon. W 16.50' S 1/4 Sec. 34, T4N, R12W
Perod W 35.91'
C/L gravel road E-W, South 1.5'



Signed by John C. Bueche
Surveyor's Michigan License No. 13027

Date 10-14-96

11020005 PAGE 412

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971
REVISED MAY 14, 1975
REVISED JAN., 1983