

# SURVEY REMONUMENTATION

APR 29 1999

## Allegan County Remonumentation LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

### SECTION

For corners in

<u>Allegan</u> (County)	Located In:	Corner Code #
1. Public Land Survey	T <u>3N</u> R <u>13W</u>	G-1 (NE, 4)
	T _____ R _____	Monterey Twp.
	T _____ R _____	
	T _____ R _____	
2. Property Controlling in Section	S _____ T _____ R _____	
	S _____ T _____ R _____	
3. Miscellaneous Property in Sec.	S _____ T _____ R _____	
	S _____ T _____ R _____	
4. Lot No. _____, Recorded Plat _____		
5. Private Claims _____		

FILED

1/28/1999 2:44:39 PM

JOYCE A. WATTS  
REGISTER OF DEEDS  
ALLEGAN COUNTY, MICH

Register of Deeds Stamp & File Number

LIBR00006 PAGE 5 18

I, John C. Bueche, in a field survey on April 13, 19 98, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

**NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.**

A. Description of original monument and accessories and/or subsequent restoration:

G-1 GLO, 1831	LCRC 1-262, May, 1972
Lucius Lyon, DS	Ratekin
To N. boundary	Fnd. 3/4" iron
86 W. of post (56.76")	PP S 45° W 31.5'
B. Ash 8" S 59 E 8	14" Hickory S 67° E 54.6'
B. Ash 21" S 62 W 22	24" Ash N 67° E 83.0'
	PP North 79.2'

1989  
Iron in Mon. Box

APPROVED REMONUMENTATION CORNER  
P.A. 345 OF 1990  
ALLEGAN COUNTY  
DATE APPROVED APR 29, 1998  
COUNTY REP. [Signature]

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

G-1 Found 3/4" rerod in Mon. Box on Twp. Line between (G-13 & F-13) 4-13  
56.95' West of G-13 (SE 33, 4-13)

Peer group approved 6-9-98.  
Traverse 2649.03'

And is accepted as a careful and faithful perpetuation of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

G-1 Replaced 3/4" rerod with 3/4" x 24" Pin with Allegan Co. Cap in Mon. Box  
Nail & Allegan Co. Remon. Tag in N side 14" Elm S 80° E 192.84'  
Dbl. headed Nail in N side 30" Blue Ash N 60° E 216.35'  
Nail & Allegan Co. Remon. Tag in W side 12" Elm S 65° E 115.06'  
Nail & Allegan Co. Remon. Tag in W side UP S 25° E 126.17'  
NE cor. siding of bldg. S 50° W 128.33'  
On C/L gravel road West; on C/L bit. road S. extended N.; C/L bit. N-S is East 37°  
Allegan Co. Mon. in Mon. Box G-13 (SE 33, 4-13) East 56.95'



Signed by John C. Bueche Date 5-8-98  
John C. Bueche, P.S. 13027  
Surveyor's Michigan License No. \_\_\_\_\_

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971  
REVISED MAY 14, 1975  
REVISED JAN., 1983

G-1  
MONTEREY TWP.

SURVEY  
REMONUMENTATION

APR 2-9 1933


SECTION

Remon 4-239

Sec 33

Salem Twp 4-13

Sec 34



Sec 4

Sec 3

Monterey Twp 3-13

