

APR 07 1998

SECTION

ALLEGAN C. REMONUMENTATION
LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in Allegan County

ALLEGAN
(County)

Located in:

Corner Code #

1. Public Land Survey

T R
T R
T R
T R

✓ EF-13 Monterey Twp

(SEQ #3)

✓ EF-1 ALLEGAN TWP.

2. Property Controlling
in SectionS-33 T-3N R-13W
S-4 T-2N R-13WMonterey Twp
Allegan Twp3. Miscellaneous
Property in Sec.S T R
S T R

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____

5. Private Claims _____

I, ARTHUR W. BRINTNALL, in a field survey on 17 NOV. 1997, do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law, established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2		6		5		4		3		2		1	
3													
4		7		8		9		10		11		12	
5													
6		18		17		16		15		14		13	
7													
8		19		20		21		22		23		24	
9													
10		30		29		28		27		26		25	
11													
12		31		32		33		34		35		36	
13													

A. Description of original monument and accessories and/or subsequent restoration:

EF-13 (SEQ. NO. 3) / EF-1 (SEQ. NO. 1)
WEST SIDE SECTION-33, T-3N, R-13W
-40.00 SET QUARTER SECTION POST ON
BORDER OF LAKE
-80.00 COR. SECTIONS 32 & 33 IN LAKE

MEANDER TRAVERSE OF LAKE BEGINS
AT 1/4 (F-13) IN G.L.O. NOTES

OCT. 31, 1997
D.R. PITS, JR., P.S.
-SET CONC. MON. W/CAP 643.86' WEST OF F-13
(T-3N, R-13W) ON LINE BETWEEN F-13 AND
SEQ NO. 1 (L-0005, PG-101) ON W. SIDE DUMONT LAKE

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:


EF-13 (SEQ. NO. 3) / EF-1 (SEQ. NO. 1)
FOUND CONCRETE MONUMENT WITH CAP 637.00' W OF F-13 ON LINE BETWEEN F-13 & SEQ #1
SKETCH ON BACK OF CERTIFICATE
REPLACED CAP W/ALLEGAN CO. REMON CAP. THIS POSITION NOT ESTABLISHED BY G.L.O.
THIS MONUMENT IS ACCEPTED AS THE BEST AVAILABLE EVIDENCE OF THE POSITION
OF THE CORNER.

-APPROVED BY ALLEGAN PEER GROUP 11 NOV. 97

APPROVED REMONUMENTATION CORNER
P.A. 345 OF 1990
ALLEGAN COUNTY
DATE APPROVED 11-11-97
COUNTY REP. K.V.O.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

EF-13 (SEQ. NO. 3) / EF-1 (SEQ. NO. 1)
CONCRETE MONUMENT WITH ALLEGAN REMONUMENT CAP
-16D & REMON TAG SOUTHEAST SIDE 10" ELM S85°E 42.25'
-16D & REMON TAG SOUTH SIDE TWIN 8" MAPLE N45°E 30.60'
-16D & REMON TAG SOUTH SIDE OF TWIN 8" WILLOW N35°E 23.50'
-16D & REMON TAG WEST SIDE 12" WILLOW N20°W 61.61'
-EAST EDGE DUMONT LAKE WEST 6'+
-SOUTH EDGE COUNTY PARK LAWN NORTH 39'+
-F-13 (T-3N, R-13W) EAST 637.00'
-SEQ NO. 1 (T-3N, R-13W) WEST 5334.74'



Signed by Arthur W. Brintnall
PREIN & NEWHOF
Surveyor's Michigan License No. #28407

Date Dec. 2, 1997