

Allegan County Remonumentation
LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in
Allegan
(County)

Located in:

Corner Code ~~11~~

1. Public Land Survey

T 4N R 11W

C-7 (SE cor. 18)

T R

Leighton Twp.

T R

T R

2. Property Controlling
in Section

S T R

S T R

3. Miscellaneous
Property in Sec.

S T R

S T R

4. Lot No. _____ Recorded Plat _____

5. Private Claims _____

1. Steven Koerber in a field survey on October 3, 1996
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the
current manual of survey instructions of the United States Department of the Interior, Bureau of Land
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a
Court of Law, established, re-established, monumented, re-monumented, recovered, found as
expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessions and/or subsequent restoration:

C-7 GLO Sylvester Sibley DS 1831
Butternut 7 S68 1/4 E 42
DO 9 N66W 27

1. June 11 1870
Old Notes by E. Strong DS
Stone 12x6x7
Elm 8 S71°E 115

2. Old County Surveyor Notes
(no date)
RR Spike
E. End N. Girder 47.55 NW
E. End S. Girder 47.55 SW

(Additional info. on back of sheet)

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

C-7 Found RR Spike
E. End N. Girder 47.55 NW
E. End S. Girder 47.55 SW

This corner is accepted as a careful and faithful perpetuation of the position of the original corner.
Peer Group approval October 8, 1996.

APPROVED REMONUMENTATION CORNER
P.A. 345 OF 1990
ALLEGAN COUNTY
DATE APPROVED 10-8-96
COUNTY REP. *Steve Koerber*

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

C-7 Replaced RR Spike with Allegan Co. Mon. (3/4" x 24" Iron Rod with Remonumentation cap)
Nail & Allegan Co. Remon. Tag in W. side 16" Ash S30°W 46.73'
Nail & Allegan Co. Remon. Tag in E side 12" stem of Maple clump S0°E 70.73'
Nail & Allegan Co. Remon. Tag in W side 14" stem of Maple clump S20°E 93.53'
Nail & Allegan Co. Remon. Tag in W. side 10" Box Elder N40°E 64.26'
B-7, T4N, R11W 2639.12'
D-7, T4N, R11W 2652.08'



Signed by *Steve Koerber*
Surveyor's Michigan License No. 39085

Date 12-10-1996

USE 0005 PAGE 432

Page 1 of 2

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 22, 1971
REVISED MAY 14, 1978
REVISED JAN., 1983

C-7, T4N, R1W
3. October 3 1974
Don Ratekin
Rec Survey L. (bad print can't read date)
wils same as No. 3 above

4. November 8, 1974
L.C.R.C. L. 3, Pg. 21
Don Ratekin
Found stake & RR. Spike
wils same as No. 3 above