

APR 07 1998

SECTION

Allegan County Remonumentation
LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Allegan
(County)

Located in:

Corner Code #

1. Public Land Survey

T 4N R 14W

A-1 (NW, 6)

T 4N R 15W

Overisel Twp.

T 4N R 15W

M-1 (NE, 1)

T 4N R 15W

Fillmore Twp.

2. Property Controlling
in Section

S 4N T 4N R 14W

S 4N T 4N R 15W

3. Miscellaneous
Property in Sec.

S 4N T 4N R 14W

S 4N T 4N R 15W

4. Lot No. _____, Recorded Plat _____

5. Private Claims _____

I, John C. Bueche, in a field survey on May 6, 19 97,
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned
in lines 1 and 2 above were in conformance with regulations and rules theretofore as required in the
current manual of survey instructions of the United States Department of the Interior, Bureau of Land
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a
Court of Law; established, re-established, monumented, re-monumented, recovered, found as
expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

A-1 GLO	LCRC L3, P393	Card file
Oct. 29, 1831	Dec., 1984	PP NW 70.8'
Lucius Lyon, DS	1/2" steel rod	St. sign NW 41.0'
80.00 set temp.	PP NW 71.00'	PP SSW 165.18'
cor. post	PP SE 58.65'	TP NE 44.2'
	PP SW 165.40'	TP SSE 106.9'
	Solid iron in mon. box	
	E 2140.19' N 1/4 6	

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

A-1 Found Ottawa Co. Mon. in Mon. Box @ C/L X (Iron E 20')
As per above wit.
Meas. East 2140.20' N 1/4 6

And is accepted as a careful and faithful perpetuation of the position of the original corner.

Peer group approved May 13, 1997.

APPROVED REMONUMENTATION CORNER
P.A. 345 OF 1990
ALLEGAN COUNTY
DATE APPROVED 5-13-97
COUNTY REP. K.V.O.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

A-1 Ottawa Co. Mon. with alum. cap in Mon. Box
C/L hyd. N 50° E 63.26'
Nail & Ottawa Co. Remon. Tag in S side PP N 60° W 71.14'
Nail & Ottawa Co. Remon. Tag in S side GP S 57° E 58.74'
Nail & Ottawa Co. Remon. Tag in W side PP S 20° W 165.37'
Nail & Allegan Co. Remon. Tag in W side PP N 8° E 205.58' (4' high)
Iron East 20.0'
On C/L bit N-S, E-W



Signed by John C. Bueche, P.S. 13027
Surveyor's Michigan License No. _____

Date 10-22-97

175

Sheet 1 of 2

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971
REVISED MAY 14, 1975
REVISED JAN., 1983

