

SURVEY & REMONUMENTATION

APR 29 1996

ALLEGAN COUNTY REMONUMENTATION LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Allegan
(County)

Located in: Corner Code

1. Public Land Survey T 4N R 14W F-11
T R S 1/4 Cor.
T R Sec. 28
T R N 1/4 Cor.
2. Property Controlling S T R Sec. 33
in Section S T R Overisel Twp.
3. Miscellaneous S T R
Property in Sec. S T R

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat
5. Private Claims

I, Kirk L. Van Order, in a field survey on October 12, 1995, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law, established, re-established, monumented, re-monumented, recovered, found as expressed below.

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
2													
3													
4													
5													
6													
7													
8													
9													
10													
11													
12													
13													

A. Description of original monument and accessories and/or subsequent restoration:

F-11
•GLO West correct between Sec. 28 & 33 39.32
Set 1/4 section post
Beech 36 N6W 27
Sycamore 36 S,SE 33
•T.O. Williams survey dated 1891, 40.765 chains to center of Sec. 33

(continued on back of sheet)

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

F-11
Fd. star drill in mon. box by using ties from Mar. 14, 1989 survey
And is accepted as a careful and faithful perpetuation of the position of the original corner.
Peer group approved May 9, 1995.

APPROVED REMONUMENTATION CORNER
P.A. 345 OF 1990
ALLEGAN COUNTY

DATE APPROVED 5-9-95
COUNTY REP. Kirk L. Van Order

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:


F-11
Removed star drill and set a standard Allegan Co. Remon. monument (3/4" x 24" steel rod w/red cap #23520) in mon. box
NW cor. conc. porch slab AZ. 139°55' 128.91'
Nail & Remon. tag SW side power pole AZ. 145°44' 96.71'
Nail & Remon. tag E side power pole AZ. 196°18' 224.49'
Nail & Remon. tag SW side power pole AZ. 310°30' 71.89'

Signed by Kirk L. Van Order Date 12-13-95
Surveyor's Michigan License No. 23520

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JULY 26, 1971
REVISED MAY 14, 1978
REVISED JAN., 1992

0005 PAGE 265

Page 1 of 2



Section A (continued from Page 1)F-11

- Hugh McDougall notebook early 1900's
 - Stone at corner
 - Maple 12 SE 46
 - Apple 10 SE 96.5
- LCRC recorded in L. 003, P. 332 by John P. Clapp, dated Mar. 10, 1982
 - Set steel bar at recorded distance from existing central quarter corner Sec. 33 (40.765 chains by T.O. Williams in 1897)
- Kirk L. Van Order survey dated Mar. 14, 1989
 - Fd. star drill in mon. box
 - NW cor. house SE 123.25'
 - NE cor. conc. hdwl. S,SE 77.20'
 - Power pole NW 72.08'
 - Tele. pole NE 63.60'
- Kirk L. Van Order survey dated June 24, 1993
 - Fd. star drill in mon. box (same ties as Mar. 14, 1989 survey)