

ALLEGAN COUNTY REMONUMENTATION
LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Allegan (County)

Located In:

Corner Code #

1. Public Land Survey

T 4N R 15W

C-1 (NW Sec 5)

T R

Fillmore Twp.

T R

T R

2. Property Controlling
in Section

S T R

S T R

3. Miscellaneous
Property in Sec.

S T R

S T R

4. Lot No. , Recorded Plat

5. Private Claims

I, David R. Greer, in a field survey on December 13, 1995, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

C-1

Government Notes 1831

Post

Ironwood 5" S46°E 10 links

Beech 8" S23°W 22 links

NOTE: This certificate supercedes the one recorded in Liber 4, Page 277, December 30, 1993 which contained an error.

Recorded in Liber 1, Page 134, Oct. 28, 1971

CL Manhole S45°W 34.00'

CL Mon. Box N85°E 5.40'

Recorded in Liber 2, Page 45, Nov 21, 1972

MSHD Nail in Power Pole ENE 73.38'

Traffic Light Guy Pole SW 39.17'

Telephone Pole SE 68.33'

Iron in Mon Box ENE 5.28'

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

C-1

Found 3/4" rod in monument box and accepted it as a careful and faithful perpetuation of the position of the original corner

Power Pole NW 62.20'

30" Maple N 71.48'

MSHD in Power Pole ENE 73.38'

Traffic light in Guy Pole SW 39.17'

Iron in Mon Box ENE 5.28'

CL Manhole S45°W 34.00'

This closing corner is 0.91 South of the South line of Sec. 31, T5N, R15W

APPROVED REMONUMENTATION CORNER

P.A. 345 OF 1990

ALLEGAN COUNTY

DATE APPROVED 3-9-94

COUNTY REP. David R. Greer



C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

C-1 Replaced steel bar in monument box with A.C. Remonumentation Iron & Cap. AZ - Michigan State Grid Direction

Iron in Mon Box C-13 SW Cor Sec 32 T5N R15W

AZ. 80°50' 5.28'

NE Cor Brick Building

AZ. 237°31' 76.68'

CL Steel Post AZ 337°05'57" 40.20'

SE Cor Brick Building

AZ. 214°10' 127.51'

SE Cor Bldg AZ 58°46' 192.22'

NW Cor Brick Foundation

AZ. 114°23' 143.01'

NE Cor Building Foundation

AZ. 107°33' 148.04'

SW Cor Building Foundation

AZ. 187°03' 189.98'

Fnd Nail & Tag N Side Power Pole

AZ. 70°00' 73.31'

Set O.C. Remon Nail & Tag E Side 30" Maple

AZ. 343°13' 71.39'

South line Sec 31, T5N, R15W

AZ. 359°41'10" 0.91'

Signed by David R. Greer
Surveyor's Michigan License No. 16042

Date 12/12/95

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971
REVISED MAY 14, 1975
REVISED JAN., 1983

W:\Data\Survey\Remon.doc

LIBER 0005 PAGE 378