

DEC 10 1993

007739

1993 ALPENA COUNTY REMONUMENTATION COMMISSION

RECORDED
ALPENA COUNTY MI.

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Alpena

(County)

Located In:

Corner Code ##

1. Public Land Survey T 32N R 8E E-6
T R
T R
T R
2. Property Controlling S T R
in Section S T R
3. Miscellaneous S T R
Property in Sec. S T R

4. Lot No. , Recorded Plat

5. Private Claims

DEC 7 9 20 AM '93

Mary A. Johnston
REGISTER OF DEEDS

Register of Deeds Stamp & File Number

I, Daniel T. Kibbe, in a field survey on July 1, 1993, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

- 1855: G.L.O. Re-survey by Josiah Knauer - set post and referenced: Sugar 12 - N59 1/2E - 13 / Sugar 6 - S42W - 15.
1890: County survey by Wm. H. LeRoy - Found roots of sugar N.B.T.
1909: County survey by Jos. W. McNeil - Found post in center of road bed.
1976: Survey by David Guthrie - Found 1 1/2" steel pin and referenced.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

- 1993: Found 1/2" rebar 5' East of the Center of French Road, 3' North of fence line West and 3' South of fence line East. This corner position is very compatible with former county surveys and is a reference for local surveys.
The found rebar is beside a 1 1/2" pin, 0.5' deep.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

- 1993: Set 1/2" x 18" iron rod with 3" aluminum cap stamped to identify the corner.
Referenced:
West - Corner post - 38.88 feet
East - 5" White Pine - 61.05 feet
S45°E - 8" White Pine - 81.70 feet
N58°W - 4" Scotch Pine - 49.52 feet

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	8	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

Signed by

Daniel T. Kibbe

Date November 24, 1993

Surveyor's Michigan License No. 37278

