

DEC 03 1993

005684 RECORDED ALPENA COUNTY MI.

COMMISSION
1993 Alpena County Remonumentation Corner

LIBER 1 PAGE 251
SEP 10 9 39 AM '93

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

Myriam A. Johnston
REGISTER OF DEEDS

For corners in

Alpena

(County)

Located In:

Corner Code -#

- | | | |
|------------------------------------|------------|-----|
| 1. Public Land Survey | T 32N R 8E | E-7 |
| | T R | |
| | T R | |
| | T R | |
| 2. Property Controlling in Section | S T R | |
| | S T R | |
| 3. Miscellaneous | S T R | |
| Property in Sec. | S T R | |

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

I, David B. Guthrie in a field survey on July 12, 19 93, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law, established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

- 1855: G.L.O re-survey by Josiah Knauer - Set post and referenced: Sugar 10 - S45½E - 20 / Sugar 10 - N43½W - 25.
1887: County survey by Fred A. Rice - Found G.L.O Corner
1977: Survey by David B. Guthrie - Found ½" iron rod and referenced.
1981: Survey by Duane R. MacNeill - Found ½" iron rod and referenced.
1989: Survey by Gary W. St.Charles - Found ½" iron rod and referenced and re-recorded. L.C.R.C., Liber 1, page 201.
1991: Survey by David B. Guthrie - Found ½" iron rod in Monument Box - Verified prior references.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

- 1993: Found ½" iron rod in Monument Box. This corner lies in the road intersection and is compatible with former county surveys. It is a reference for local surveys.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

- 1993: Set ½" x 24" iron rod with a 3" aluminum cap stamped to identify the corner. Referenced:
N71°E - Utility Pole - 58.25 feet
S39°E - Utility Pole - 70.48 feet
N45°W - Anchor Pole - 55.29 feet
N30°E - 4" Scotch pine - 101.23 feet



Signed by *David B. Guthrie*

Date 9/10/93

Surveyor's Michigan License No. 22435