| | LAND CORNER RECORDATION Filing Requirement of Act 74, M | | REGISTER OF DEED | No 30 | ANTRIA |
|---|---|--------------|------------------|--|---------------------|
| For corners in | | | m p | 4 | |
| ANTRIM (County) | Located In: SEC24 Corner Code ## | | R ? | 4 00 PN '94 | COUNTY OR RECORD |
| 1. Public Land Survey | T 30N R 7W L-9 | | m E | 35 | 8 J |
| | <u> Τ</u> | _ | SA | 望 | 8 |
| | T | | | | |
| | T R SUNVEY & | | | | |
| 2. Property Controlling S in Section S | B T R PTM MINISTRA | 7NI | | | |
| , = = = = | T R | | Deeds Stan | na e Eila | Numbar |
| Property in Sec. S | T R Company | negister of | Deens Stall | | Number |
| | | | | | |
| 4. Lot No, Reco | rded Plat | A B | C D E | F G H | IJKL |
| 5. Private Claims | SECTION - | | | 57 & L | |
| | | 2 - 6 | 5 5 | : <u>-</u> -3- | 1-2-1-1- |
| | | 1 | | | |
| NETT T MAY | A COR E | 1 7 | | | 1-11-1-12- |
| | a field survey on OCT 5 15 ments of P.A. 74, Michigan P.A. of 1970, the corner points | | . 8 6 | | |
| in lines 1 and 2 above were in cor | nformance with regulations and rules therefore as req | uired in the | 17-1-10 | 3———15—— ——————————————————————————————— | f1413 |
| | ns of the United States Department of the Interior, Bur | | | \$1 | 1 |
| | urt of Law and/or that the corner points mentioned in line e-rules of the Michigan Board of Land Surveyors or by a | | 20-1-2 | 22- | 23 - 24 |
| Court of Law; established, re-es | tablished, monumented, re-monumented, recovered | i, found as | | Ç8 | |
| expressed below: | | 1030- | 2928 | 27 | 26 -25 |
| | ers, all in the same town and range, may be reco | I I | - 3 | | |
| on this certificate. | | 12 -31 | 32 33 | 34 | -35 -36 |
| A Description of original mon | ument and accessories and/or subsequent resto | ration: | | | |
| A. Description of original mon | | | 1 | | |
| g | | | | | 1 - 1 - 4 - 1 - 13 |
| GLO SET CORNER | POST OCT 1855 | | | | - |
| | | | | ***** | |
| BEECH 9 N3 | | | | | |
| SUGAR 18 S54 | W v 22 | | | | |
| | | • | | e de la composition della comp | |

NO EVIDENCE FOUND

- B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:
- FOUND 1 IRON AND CAP #14200 CHARNARD

Ratiffied by Peer Group Arthur L. Lennox

Date: Oct. 6, 1994

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

SET COUNTY MONUMENT

N34W 29.17' MPL 6"

N12E 34.32' MPL 8" N75W 27.85' MPL 4" S18E 19.11' BASSWOOD 14"



Date NOV

Surveyor's Michigan License No.

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971 REVISED MAY 14, 1975 REVISED JAN., 1983