

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. PA 1970

For Corners In:

Arenac

(County)

Located In

Corner Code #

1. Public Land Survey T 19N R 3E C2
T R
2. Property Controlling in Section S T R
S T R
3. Miscellaneous Property in Section S T R
S T R

4. Lot No: Recorded Plat:

5. Private Claims:

I, Craig W. McVean, in a field survey on Feb. 22, 2005 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

C2 - GLO - Set 1/4 Post - J. Mullett - 1846

W. Pine 12" S47°E 27 L.

W. Pine 6" N47°W 14 L.

- CPC Survey - Drawing # SF16944 - Sheet 98

Corner set - 1968

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

C2 - 1/4 Corner common to Sec. 6 & 5 - No conclusive GLO evidence. No evidence of Consumer's iron. Set 4" DNR Alum. Cap on 1" x 36" Galv. iron pipe single proportion to GLO between 'C1' and 'C3'. This fits Consumer's position. Also found Consumer's 'T' iron 330' west per their survey drawing. Centerline of N-S Powerline is 24' W. Centerline of N-S overhead tower powerline is 114' ± W. DNR Mon. accepted as a careful and faithful re-establishment of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

C2 - 4" DNR Alum. Cap on 1" x 36" Galv. iron pipe

Set Blue Carsonite Post 1' E

S85°E 41.76' to set N & T in N. side 4" scrub Cherry clp.

S67°E 59.79' to set N & T in S. side 15" Tw. Oak

S22°E 88.45' to set N & T in NE side 4" Tamarack

