

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

(BARAGA COUNTY)		CORNER CODE NUMBER
FOR CORNERS OF--	LOCATED IN--	
1. PUBLIC LAND SURVEY_____	T. <u>47</u> N. <u>34</u> E. <u>W.</u>	<u>F-9</u>
2. PROPERTY CONTROLLING IN SECTION <u>28</u>	T. <u>47</u> N. <u>34</u> E. <u>W.</u>	<u>2</u>
3. MISCELLANEOUS PROPERTY IN SECTION _____	T. _____ N. _____ E. _____	
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND
FILING NUMBER

I, Keith L. Sackett, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on June 23, 1980, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

Corner F-9: Original monument and accessories not found. Found old post by Northern Paper Mills 1946. Many old blazes and one squared cedar tree.

Corner 2: Not set on original survey nor subsequently, apparently.

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

Corner F-9: Reestablished at old wood post. Corner fits good with other corners in area.

Corner 2: Established midway on line between corners east and west.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Corner F-9: Set 1" I.D. x 36" I.P. with 4" aluminum cap.

12" Ash S46W 6.5 ft., 1/4S, NBT
6" Cedar S67E 14.5 ft., 1/4S, NBT
9" Cedar N15E 9.6 ft., 1/4S, NBT

Corner 2: Set 1" I.D. x 36" I. P. with 4" aluminum cap.

7" Sugar N15E 11.8 ft., 1/16S, BT
5" Sugar S40E 27.3 ft., 1/16S, BT
7" Sugar S20W 15.6 ft., 1/16S, BT

SIGNED BY _____ DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

(SEAL)

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____

APPROVED AND SIGNED BY Keith L. Sackett
CHIEF OF SURVEY PARTY
MICHIGAN REGISTERED LAND SURVEYOR
Keith L. Sackett

DATE 9 3 80

