

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Baraga (County)	Located In:	Corner Code #
1. Public Land Survey	T R	
	T R	
	T R	
2. Property Controlling in Section	S 20 T 47N R 34W	5
	S 20 T 47N R 34W	D8
	S T R	
3. Miscellaneous Property in Sec.	S T R	
	S T R	
4. Lot No. _____, Recorded Plat		
5. Private Claims		

Register of Deeds Stamp & File Number

1	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

I, Stephan J. Szyszkoski, in a field survey on 08/14/12 do hereby state  
that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2  
above were in conformance with regulations and rules therefore as required in the current manual of survey  
instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of  
a Court of Law and for that the corner points mentioned in lines 3, 4 and 5 above were in conformance with  
the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established,  
re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded  
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(5-Sec. 20) North 1/16 corner, Sec. 20. Not previously monumented.

(D8) Center of Section 20. Not previously monumented.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(5-Sec. 20) Established the position for the corner midway and on a straight line between Quarter  
corner 1305.38' north and Center of Section 20 1305.38' south.

(D8) Established the position for the corner at the intersection of straight lines connecting  
opposite 1/4 corners.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(5) Set 1"IDx32" I.pipe with 4" alum. MDNR cap.  
Set measuring nail with MDNR tag in the side of:  
11" Cedar N12°E 13.3' mrkd "1/16S BT"  
6" Maple S84°E 15.9' do  
12" Maple S23°W 3.2' do  
15" Cedar N27°W 17.3' do  
Set sq'd cedar post adjacent.

(D8) Set 1"IDx32" I.pipe with 4" alum. MDNR cap.  
Set measuring nail with MDNR tag in the side of:  
16" Cedar N45°E 11.0' mrkd "C1/4 BT"  
6" Hemlock S49°E 36.8' do  
11" Cedar S26°W 13.3' do  
6" Bl. Ash N65°W 4.8' do  
Set sq'd Cedar post adjacent.

Bearings are magnetic.

Signed by Stephan J. Szyszkoski  
Surveyor's Michigan License No. 33986

Date 01/02/2013

For the Michigan Department of Natural Resources, Forest Resources Division

