

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Baraga (County)	Located In:	Corner Code #
1. Public Land Survey	T 47N R 34W	D6
	T 47N R 34W	D5
	T R	
2. Property Controlling in Section	S T R	
	S T R	
3. Miscellaneous Property in Sec.	S T R	
	S T R	

Register of Deeds Stamp & File
Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims

D5 May 19 2004
D6 May 18 2004

I, Stephan J. Szyszkoski, in a field survey on _____, 20____ do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(D6) Center of Section 17. Not established in the original survey,
(D5) Quarter corner common to Sections 8-17. 1852: Established by Z.B.Searles: [East] "corrected btwn Secs 8&17...39.765 Set quarter Sec. Post. Fir 8 S22E 9 links, Maple 8 N67W 16 links...79.53 Section Corner."

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(D6) Established the corner at the intersection of straight lines connecting opposite Quarter corners.
(D5) The original post and accessories were not recovered. Reestablished the corner by single proportionate measurement to the original record between Section corners 2619.16' East and West.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(D6) Set 1" IDx32" I.pipe with 4" alum. MDNR cap. Blazed, scribed, and set measuring nails in:	(D5) Set 1" IDx32" I.pipe with 4" alum. MDNR cap. Blazed, scribed, and set measuring nails in:
9" Cedar N14E 53.2' "C1/4 8T"	5" Balsam N22E 1.8' "1/4S NBT"
9" Sugar N45E 42.0' do	11" Cedar N60E 32.1' do
8" Maple S75E 9.9' do	10" Cedar S35E 29.6' do
13" dbl Oak N30W 40.7' do	7" Spruce S63W 9.0' do
Set sq'd cedar post adjacent. Bearings are magnetic. Distances are to nail with tag.	Set sq'd cedar post adjacent. Bearings are magnetic. Distances are to nail with tag.



Signed by Stephan J. Szyszkoski
Surveyor's Michigan License No. 33986

Date 7/1/04

For the Michigan Department of Natural Resources, Office of Land and Facilities