

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

| Baraga (County) | Located In: | Corner Code # |
|---------------------------------------|---|---------------|
| 1. Public Land Survey | T _____ R _____ T _____ R _____ T _____ R _____ | _____ |
| 2. Property Controlling in Section | S 17 T 48N R 32W S 17 T 48N R 32W S _____ T _____ R _____ | 7 D6 |
| 3. Miscellaneous Property in Sec. | S _____ T _____ R _____ S _____ T _____ R _____ | _____ |
| 4. Lot No. _____, Recorded Plat | | |
| 5. Private Claims | | |

I, Stephan J. Szyszkoski, in a field survey on 7 03/08/2012
D6 03/15/2012 do hereby state
that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2
above were in conformance with regulations and rules therefore as required in the current manual of survey
instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of
a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with
the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established,
re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(7-Sec. 17) North 1/16 corner, Section 17. Not previously monumented.

(D6) Center of Section 17. Not previously monumented.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(7-Sec. 17) Established the position for the corner midway and on the Section line between Quarter
corner 1330.72' south and Section corner 1330.72' north.

(D6) Established the position for the corner at the intersection of straight lines connecting
opposite 1/4 corners.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(7) Set 1"IDx32" I.pipe with 4" alum. MDNR cap.
Set measuring nail with MDNR tag in the side of:
7" Balsam N01W 30.6' mrkd "1/16S BT"
4" Balsam N65E 7.55' do
4" Balsam S25W 10.3' do
3" Cherry N54W 11.65' do
Set sq'd cedar post adjacent.
Bearings are magnetic.

(D6) Set 1"IDx32" I.pipe with 4" alum. MDNR cap.
Set measuring nail with MDNR tag in the side of:
3" Balsam N12W 13.3' mrkd "C1/4 BT"
5" Balsam S81E 3.9' do
14" Cedar S14E 20.95' do
18" Cedar S84W 26.5' do
Set sq'd cedar post adjacent.
Bearings are magnetic.

Signed by Stephan J. Szyszkoski
Surveyor's Michigan License No. 33986

Date 04/04/2012

For the Michigan Department of Natural Resources, Forest Resources Division

