

LAND CORNER RECORDATION CERTIFICATE

ARAGA COUNTY

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF --:	LOCATED IN --:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. _____ N. _____ E. _____ S. _____ R. _____ W. _____	
2. PROPERTY CONTROLLING IN SECTION 36	T. 49 N. 31 X. W. _____	10, 15, 11
3. MISCELLANEOUS PROPERTY IN SECTION	T. _____ N. _____ E. _____ S. _____ R. _____ W. _____	
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Keith L. Sackett, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on 2-17-83, 19____, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

Corner 10: Not set on original survey nor subsequently apparently.
 Corner 15: Not set on original survey nor subsequently apparently.
 Corner 11: Not set on original survey nor subsequently apparently.

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

Corner 10: Established midway and on line between 1/4 corner north and section corner south.
 Corner 15: Established midway and on line between 1/4 corner east and section corner west.
 Corner 11: Established during section subdivision.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Corner 10: Set 1" ID by 32" I. P. with 4" aluminum cap.	Corner 11: Set 1" I.D. by 32" I.P.
7" Sugar S12W 22.4 ft. 1/16 S, BT	w/4" alum, cap.
12" Sugar N 75W 23.2 ft. 1/16S, BT	8" Sugar S68E 14.1 ft. 1/16S, BT
4" Sugar N 82E 19.2 ft. 1.16S, BT	7" Sugar S25W 12.1 ft. 1/16S, BT
Corner 15: Set 1" I.D. by 32" I.P.	6" Sugar N15E 14.0 ft. 1/16S, BT
w/4" alum. cap.	
5" Sugar N15E 4.6 ft. 1/16S, BT	
6" Sugar N56W 30.3 ft. 1/16S, BT	
12" W. Birch S50E, 7.8 ft 1/16S, BT	

SIGNED BY _____ DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

(SEAL)

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____

APPROVED AND SIGNED BY Keith L. Sackett DATE _____

CHIEF OF SURVEY PARTY

MICHIGAN REGISTERED LAND SURVEYOR

(SEAL)

Keith L. Sackett
 Department of Natural Resources

SURVEYOR'S MICHIGAN REGISTRATION NO. 19006