

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

For corners in
Baraga

(County)

Located In:

Corner Code: #

1	Public Land Survey	T 49N	R 32W	C12
		T	R	
		T	R	
		T	R	
		T	R	
2	Property Controlling in Section	S 32	T	R
		S	T	R
3	Miscellaneous Property in Sec	S	T	R
		S	T	R

Register of Deeds Stamp & File Number

4 Lot No. _____, Recorded Plat _____
5 Private Claims _____

I, Keith Sackett, in a field survey on September 29, 19 88, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law, established, re-established, monumented, re-monumented, recovered, found as expressed below

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A Description of original monument and accessories and/or subsequent restoration:

C12	16	10	3
Original monument and accessories not found.	Not set on original survey nor subsequently, apparently.	Not set on original survey nor subsequently, apparently.	Not set on original survey nor subsequently, apparently.

B Description of corner evidence found and/or method applied in restoring or reestablishing corner:

C12	16	10	3
Restored midway on line.	Established midway on line.	Established midway on line.	Established midway on line.

C Description of monument for corner and accessories established to perpetuate locating the position of the corner:

C12	16	10	3
Set 1" I.D. x 36" I.P. w/4" aluminous cap.	14" w.pine N46E 2.9' 1/16s BT	9" balsam N27E 10.0' 1/16s BT	10" sugar N09W 7.2' 1/16s BT
12" white pine S82W 22.1' 1/4s NBTs	12" w.pine S37W 13.5' 1/16s BT	12" spruce S42E 30.5' 1/16s BT	9" sugar S22W 3.1' 1/16s BT
14" white pine S25W 18.3' 1/4s NBTs	16" w.pine N10W 27.7' 1/16s BT	10" spruce S80W 11.4' 1/16s BT	10 hemlock N72E 10.8' 1/16s BT
11" sugar S42E 6.2' 1/4s NBTs	Set 1" I.D. 36" I.P. w/4" ALUM. CAP	Set 1" I.D. 36" I.P. w/4" ALUM. CAP	Set 1" I.D. 36" I.P. w/4" ALUM. CAP

Signed by Keith Sackett Date 12-19-88

Surveyor's Michigan License No 19006