## LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

## For corners in

			1					
Baraga	Located In:	Corner Code #	<sub>#</sub>					
(County)	W.	W.						
1. Public Land Survey	TR		_					
2. Property Controlling in Section		34W 12 34W H8						
<ol><li>Miscellaneous Property in Sec.</li></ol>	S T R R		<u> </u>	et 15				
4. Lot No. Recorded Plat				Register of Deeds Stamp & File Number				
5. Private Claims  1. Stephan J. Szyszkoski , i	<u></u>	11/28/12 do t	hereby state	A B C	D E F (	3 H X	J K	L M
that under requirements of P.A. above were in conformance with	74, Michigan P.A. of 1970, the	e corner points mentioned in I	ines 1 and 2		-66-	-10	1/2-	-12-
instructions of the United States	Department of the Interior, Bui	reau of Land Management or by	a decree of	6 10	-1716	-15;	-	-13
a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:				B -19-	20 21	8	3	-21
NOTE: Not more than 2 corr	ners, all in the same town ar	nd range, may be recorded	1	0 30	29 28	27;	26	25
on this certificate.				2 31	32 33	34 3	5	-36
A. Description of original m	nonument and accessories	and/or subsequent restora	ation:	الساساد				
G								
(12) South 1/16 corner, 5	Section 22. Not previous	ously monumented.						

- (H8) Center of Section 22. Not previously monumented.
- B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:
- (12) Established the position for the corner midway and on a straight line between Quarter corner 1313.58' south and Center of Section 22 1313.58' north.
- (H8) Established the position for the corner at the intersection of straight lines connecting opposite 1/4 corners.
- C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(12) Set 1"IDx32" I.pipe with 4" alum. MDNR cap. (H8) Set 1"IDx32" I.pipe with 4" alum. MDNR cap. Set measuring nail with MDNR tag in the side of: Set measuring nail with MDNR tag in the side of: 6" B.Spruce N11°W 5.5' mrkd "C1/4 BT" 9" Tamarack S13°E 28.55' mrkd "1/16S BT" 13" Tamarack S80°E 18.1' do 9" B.Spruce N60°E 14.35' do 13" Tamarack N61°E 27.95' do 9" B.Spruce S62°E 11.7' do 3" Balsam N38°E 14.85' do 5" B.Spruce S53°W 2.3' do 3" sq'd and scribed post adjacent. 3" sq'd and scribed post adjacent. E=7881857.910 N=205882.820 E=7881869.799 N=206282.973

Bearings are magnetic. Coordinates are MCS83 in meters (NAD83(2011) Datum).

Surveyor's Michigan License No.

Date

33986

03/13/2013

For the Michigan Department of Natural Resources, Forest Resources Division