

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Baraga (County)	Located In:	Corner Code #
1. Public Land Survey	T R	
	T R	
	T R	
2. Property Controlling in Section	S 33 T 50N R 34W	7
	S 28 T 50N R 34W	7
	S T R	
3. Miscellaneous Property in Sec.	S T R	
	S T R	
4. Lot No. _____, Recorded Plat _____		
5. Private Claims _____		

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

I, Stephan J. Szyszkoski, in a field survey on 07/10/12 do hereby state
that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2
above were in conformance with regulations and rules therefore as required in the current manual of survey
instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of
a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with
the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established,
re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(7-Sec. 33) North 1/16 corner between Sections 33 and 34. Not previously monumented.

(7-Sec. 28) North 1/16 corner between Sections 27 and 28. Not previously monumented.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(7-Sec. 33) Established the position for the corner midway and on the Section line between Section
corner 1324.06' north and Quarter corner 1324.06' south.

(7-Sec. 28) Established the position for the corner midway and on the Section line between Section
corner 1308.65' north and Quarter corner 1308.65' south.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(7-Sec. 33)
Set 1"IDx32" I.pipe with 4" alum. MDNR cap.
Set measuring nail with MDNR tag in the side of:
18" Hemlock N28E 2.40' mrkd "1/16S BT"
18" Hemlock S05E 12.1' do
12" Sugar S76W 12.2' do
6" Hemlock N38W 20.95' do
Set sq'd Cedar post adjacent.

(7-Sec. 28)
Set 1"IDx32" I.pipe with 4" alum. MDNR cap.
Set measuring nail with MDNR tag in the side of:
12" Sugar N51E 18.0' mrkd "1/16S BT"
6" Sugar S05E 20.6' do
3" Sugar S43W 5.1' " X X "
5" Sugar N54W 3.35' "1/16S BT"
Set sq'd Cedar post adjacent.

Bearings are magnetic.

Signed by Stephan J. Szyszkoski
Surveyor's Michigan License No. 33986

Date 12/12/2012

For the Michigan Department of Natural Resources, Forest Resources Division

